

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HUT VOR/DME	SALTT LOM	358.54 / 7.61	3200
GUTER INT/HUT 20.67 DME	SALTT LOM	213.03 / 13.95	3300
SPELT INT/HUT 17.96 DME	SALTT LOM	087.39 / 16.42	3200
WUPNU/HUT 16.00 DME CW (IAF)	OSNIE/HUT 16.00 DME (NOPT)	16.00 DME ARC (HUT LR-326)	3800
ZUPAB/HUT 16.00 DME CCW (IAF)	OSNIE/HUT 16.00 DME (NOPT)	16.00 DME ARC (HUT LR-341)	3800
OSNIE/HUT 16.00 DME (IF)	SALTT LOM	134.27 / 9.65 (I-HUT)	2900

**ILS: DA
LOC: 3.98 NM AFTER SALTT LOM**

CLIMB TO 2400 THEN CLIMBING RIGHT TURN TO 3100 DIRECT HUT VOR/DME AND HOLD.

**ADDITIONAL FLIGHT DATA:
HOLD SW, LT, 038.00 INBOUND.
CHART FAS OBST: 1624 TREE 380510N/0975247W.
OBST: 1855 AAO 380718N/0975447W
CHART HUT R-245 AT WUPNU.
CHART HUT R-021 AT ZUPAB.
CHART CIRCLING ICON.
CHART PLANVIEW NOTE: ADF OR DME REQUIRED.**

MAG VAR: 4E EPOCH YEAR: 2020

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD NW SALTT LOM, LT, 134.27 INBOUND, 3200 FT. IN LIEU OF PT (IAF)
3. FAC: 134.27 FAF: SALTT LOM DIST FAF TO MAP: 3.98 THLD: 3.98
4. MIN. ALT: SALTT LOM 2900
5. DIST TO THLD FROM OM: 3.98 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 902
6. MIN GS INCPT: 2900 GS ALT AT: - OM: 2853 MM: - IM: -
7. GS ANGLE: 3.00 TCH: 47.5
8. MSA FROM: HU LOM 4000

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	ILS: STANDARD #	LOC: STANDARD @												
CATEGORY >>>>>	A		B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 13**	1725	2400	200	1725	2400	200	1725	2400	200	1725	2400	200			
S-LOC 13	1880	2400	355	1880	2400	355	1880	3000	355	1880	3000	355			
CIRCLING	2080	1	537	2080	1	537	2200	1 3/4	657	2720	3	1177			

NOTES:
 CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.
 CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 22 NA AT NIGHT.
 CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 13 CAT C/D VISIBILITY TO RVR 5500.

#@ NA WHEN CONTROL TOWER CLOSED.
 # CAT C 700-2, CAT D 1200-3
 @ CAT D 1200-3



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1525 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: I-HUT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 13, AMDT 17, 12/07/2017	SUP: AMDT: 16E DATED 01/08/2015
----------------------------------	--	-------------------------------	--	---------------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1525 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: I-HUT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 13, AMDT 17, 12/07/2017	SUP:
				AMDT: 16E
				DATED: 01/08/2015

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1525 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: I-HUT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 13, AMDT 17, 12/07/2017	SUP:
				AMDT: 16E
				DATED: 01/08/2015