

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HUT VOR/DME	SAYAN (TF) (FO) (RNP 2.00)	038.32 / 17.14	3200	LNAV: RW22 CLIMB TO 3400 DIRECT IZAGI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 038.31 INBOUND. CHART FAS OBST: 1713 TREE 380526N/0975033W. CHART CIRCLING ICON. PAFNA TO RW22: 3.40/34.
STONS (IAF)	SAYAN (NOPT) (TF) (FB) (RNP 1.00)	264.83 / 12.02	3200	
GUTER (IAF)	SAYAN (NOPT) (TF) (FB) (RNP 1.00)	151.33 / 6.68	3200	
SAYAN (IF/IAF)	PAFNA (TF) (FB) (RNP 1.00)	218.54 / 6.67	3200	
PAFNA (FAF)	RW22 (MAP) (TF) (FO) (RNP 0.30)	218.47 / 4.50		
(SEE FORM 8260-10)				

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD NE SAYAN, RT, 218.54 INBOUND, 3200 FT. IN LIEU OF PT (IAF)
3. FAC: 218.47 FAF: PAFNA DIST FAF TO MAP: 4.50 THLD: 4.50
4. MIN. ALT: SAYAN 3200, PAFNA 3200
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW22 4000

MAG VAR: 4E EPOCH YEAR: 2020

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1980	1	437	1980	1	437	1980	1 1/4	437		NA				
CIRCLING	2080	1	537	2080	1	537	2200	1 3/4	657		NA				

NOTES:
 CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT STONS ON V532 NORTHBOUND AND V532 SOUTHBOUND.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON HUT VOR/DME AIRWAY RADIALS 021 CW 074.
 CHART NOTE: STRAIGHT-IN AND CIRCLING RWY 22 NA AT NIGHT.



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1543 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1, 12/07/2017	SUP: AMDT: ORIG-A DATED 01/08/2015
---	---	-------------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW22 (MAP)	1943 MSL (CA)	218.47	
1943 MSL	IZAGI (DF) (FO) (RNP 1.00)		3400



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1543 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1, 12/07/2017	SUP:
				AMDT: ORIG-A
				DATED: 01/08/2015