

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HUT VOR/DME	TURKY/HUT 9.00 DME	038.18 / 9.00	4000
YETRU/HUT 15.00 DME CW (IAF)	NUBRE/HUT 15.00 DME (NOPT)	15.00 DME ARC	3300
ZIMEX/HUT 15.00 DME CCW (IAF)	NUBRE/HUT 15.00 DME (NOPT)	15.00 DME ARC	3300
NUBRE/HUT 15.00 DME (IF)	TURKY/HUT 9.00 DME	218.18 / 6.00 (HUT R-038)	2700

**MAP: HUT VOR/DME 5.97 DME**

**CLIMB TO 3100 DIRECT HUT VOR/DME AND HOLD.**

ADDITIONAL FLIGHT DATA:  
**HOLD SW, LT, 038.00 INBOUND.**  
**CHART FAS OBST: 1723 TREE 380537N/0975045W.**  
**CHART HUT R-292 AT YETRU.**  
**CHART HUT R-128 AT ZIMEX.**  
**CHART CIRCLING ICON.**  
**TURKY TO RW22: 3.49/33.5.**  
**CHART PLANVIEW NOTE: DME REQUIRED.**

- PT L SIDE OF COURSE 038.18 OUTBOUND 4000 FT WITHIN 10 MILES OF TURKY (IAF)
- 
- FAC 218.18 FAF TURKY/HUT 9.00 DME DIST FAF TO MAP \_\_\_\_\_ THLD 3.03
- MIN. ALT TURKY 2700
- MSA FROM: HUT VOR/DME 4000

MAG VAR: **4E** EPOCH YEAR: **2020**

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
<b>S-22</b>	<b>1980</b>	<b>1</b>	<b>437</b>	<b>1980</b>	<b>1</b>	<b>437</b>	<b>1980</b>	<b>1 1/4</b>	<b>437</b>		<b>NA</b>				
<b>CIRCLING</b>	<b>2080</b>	<b>1</b>	<b>537</b>	<b>2080</b>	<b>1</b>	<b>537</b>	<b>2200</b>	<b>1 3/4</b>	<b>657</b>		<b>NA</b>				

NOTES:  
**CHART NOTE: CIRCLING TO RWY 22 NA AT NIGHT.**  
**CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.**  
**CHART NOTE: DME REQUIRED.**  
**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON HUT VOR/DME AIRWAY RADIALS 021 CW 074.**



CITY AND STATE <b>HUTCHINSON, KS</b>	ELEVATION: <b>1543</b> TDZE: <b>1543</b>	FACILITY IDENTIFIER: <b>HUT</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>VOR RWY 22, AMDT 7, 12/07/2017</b>	SUP <b>VOR/DME RWY 22</b>
	AIRPORT NAME: <b>HUTCHINSON RGNL</b>			AMDT <b>6A</b>
				DATE <b>05/12/2005</b>

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE <b>HUTCHINSON, KS</b>	ELEVATION: 1543      TDZE: 1543 AIRPORT NAME: <b>HUTCHINSON RGNL</b>	FACILITY IDENTIFIER: <b>HUT</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>VOR RWY 22, AMDT 7, 12/07/2017</b>	SUP: <b>VOR/DME RWY 22</b>
				AMDT: <b>6A</b>
				DATED: <b>05/12/2005</b>