

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HUT VOR/DME	SALTT LOM	358.54 / 7.61	3200
GUTER INT/HUT 20.67 DME	SALTT LOM	213.03 / 13.95	3300
SPELT INT/HUT 17.96 DME	SALTT LOM	087.39 / 16.42	3200

MAP: 3.98 NM AFTER SALTT LOM
CLIMB TO 2400 THEN CLIMBING RIGHT TURN TO 3100 DIRECT HUT VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SW, LT, 038.00 INBOUND.
CHART FAS OBST: 1849 TOWER 380701N/0975308W.
CHART CIRCLING ICON.
SALTT LOM TO RW13: 3.15/45.

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD NW SALTT LOM, LT, 134.27 INBOUND, 3200 FT. IN LIEU OF PT (IAF)**
- FAC 134.22 FAF SALTT LOM DIST FAF TO MAP 3.98 THLD 3.98
- MIN. ALT SALTT LOM 2900
- MSA FROM: **HU LOM 4000**

QUALITY
25
CHECKED

MAG. VAR: 4E EPOCH YEAR: 2020

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-13	2200	4000	675	2200	4000	675	2200	1 1/2	675	2200	1 1/2	675			
CIRCLING	2200	1	657	2200	1	657	2200	1 7/8	657	2720	3	1177			

NOTES:

CHART NOTE: CIRCLING TO RWY 22 NA AT NIGHT.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HUT VOR/DME ON V280 SOUTHWEST BOUND.
CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-13 CAT A/B VISIBILITY TO RVR 5500, AND CAT C/D TO 1 7/8 SM.

@ CAT D 1200-3

QUALITY
25
CHECKED

CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1525	FACILITY IDENTIFIER: HU	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 13, AMDT 16, 12/07/2017	SUP
	AIRPORT NAME: HUTCHINSON RGNL			AMDT 15B
				DATE 04/03/2014

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE HUTCHINSON, KS	ELEVATION: 1543 TDZE: 1525 AIRPORT NAME: HUTCHINSON RGNL	FACILITY IDENTIFIER: HU	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 13, AMDT 16, 12/07/2017	SUP:
				AMDT: 15B
				DATED: 04/03/2014