

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW17 CLIMB TO 3600 DIRECT ARLTT AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 353.24 INBOUND. FAS OBST: 1810 AAO 380756N/0975238W. CHART 2052 TOWER 380918N/0975248W. DISTANCE TO THLD FROM 366 HAT: 1.02 NM. CHART VDP AT 1.55 NM TO RW17* *LNAV ONLY. WAAS CHANNEL # 81941 REFERENCE PATH ID: W17A CHART CIRCLING ICON. LTP HAE: 436.3 M							
HARAN		OJILE (TF) (FB) (RNP 2.00)		080.38 / 29.62				3600									
HUT VOR/DME		DDOEE (TF) (FO) (RNP 2.00)		006.05 / 16.16				3600									
OJILE (IAF)		DDOEE (NOPT) (TF) (FB) (RNP 1.00)		112.94 / 5.00				3600									
GUTER (IAF)		DDOEE (NOPT) (TF) (FB) (RNP 1.00)		240.61 / 6.56				3600									
DDOEE (IF/IAF) (SEE FORM 8260-10)		FINGH (TF) (FB) (RNP 1.00)		173.24 / 6.40				3200									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N DDOEE, RT, 173.24 INBOUND, 3600 FT. IN LIEU OF PT (IAF) 3. FAC: 173.25 FAF: FINGH DIST FAF TO MAP: 5.14 THLD: 5.14 4. MIN. ALT: DDOEE 3600, FINGH 3200 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3200 GS ALT AT: FINGH 3200 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 39.8 34:1 IS NOT CLEAR 8. MSA FROM: RW17 4000										MAG VAR: 4E		EPOCH YEAR: 2020					
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD					
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	1889	1	366	1889	1	366	1889	1	366		NA						
LNAV/VNAV DA	2078	1 5/8	555	2078	1 5/8	555	2078	1 5/8	555		NA						
LNAV MDA	2060	1	537	2060	1	537	2060	1 1/2	537		NA						
CIRCLING	2080	1	537	2080	1	537	2200	1 3/4	657		NA						
NOTES: CHART NOTE: CIRCLING TO RWY 22 NA AT NIGHT. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON HUT VOR/DME AIRWAY RADIALS 292 CW 074.																	
CITY AND STATE HUTCHINSON, KS		ELEVATION: 1543 TDZE: 1523 AIRPORT NAME: HUTCHINSON RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG, 12/07/2017						SUP:					
												AMDT: NONE					
												DATED					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
FINGH (FAF)	RW17 (MAP) (TF) (FO) (RNP 0.30)	173.25 / 5.14	
RW17 (MAP)	1889 MSL (CA)	173.25	
1889 MSL	ARLTT (DF) (FO) (RNP 1.00)		3600

QUALITY
25
CHECKED

CITY AND STATE
HUTCHINSON, KS

ELEVATION: 1543 TDZE: 1523
AIRPORT NAME:
HUTCHINSON RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, ORIG, 12/07/2017

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KHUT
RUNWAY	RW17
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17A
LTP/FTP LATITUDE	380412.2850N
LTP/FTP LONGITUDE	0975145.9330W
LTP/FTP ELLIPSOIDAL HEIGHT	+04363
FPAP LATITUDE	380243.1895N
FPAP LONGITUDE	0975140.5235W
THRESHOLD CROSSING HEIGHT (TCH)	00039.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

AAD39226

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04643
FPAP ORTHOMETRIC HEIGHT	+04643

QUALITY
25
CHECKED

CITY AND STATE

HUTCHINSON, KS

ELEVATION: 1543

TDZE: 1523

AIRPORT NAME:

HUTCHINSON RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, ORIG, 12/07/2017

SUP:

AMDT: NONE

DATED: