# U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, StateAirportEffective DateAmdt. No.HOLDENVILLE, OKHOLDENVILLE MUNI20 OCT 2011ORIG

## **TAKEOFF MINIMUMS:**

RWY 17, 35 STANDARD.

### **TEXTUAL DEPARTURE PROCEDURES:**

RWY 35, CLIMB HEADING 353.99 TO 1400 BEFORE TURNING RIGHT.

## **TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 17, TREE 122 FT FROM DER, 370 FT RIGHT OF CENTERLINE, 17 FT AGL/871 FT MSL. SILO 910 FT FROM DER, 715 FT RIGHT OF CENTERLINE, 60 FT AGL/903 FT MSL.

NOTE: RWY 35, TREE 596 FT FROM DER, 520 FT RIGHT OF CENTERLINE, 48 FT AGL/898 FT MSL. TREE 1213 FT FROM DER, 753 FT LEFT OF CENTERLINE, 59 FT AGL/909 FT MSL.

#### **CONTROLLING OBSTACLES:**

**OBSTACLES MANDATING ODP ROUTE DEVELOPMENT:** 

RWY 35: 1280 FT MSL TOWER 350627.00N-0962355.00W.

#### **REMARKS:**

