

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES											MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW09 CLIMB TO 2000 DIRECT FORSU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 270.88 INBOUND. CHART FAS OBST: 409 TWR 261047N/0801315W CHART 219 AAO 261122N/0801550W. CHART A-291A. CHART A-291B. CHART A-291C. DISTANCE TO THLD FROM 200 HAT: 0.45 NM. CHART VDP AT 1.30 MILES TO RW09* *LNAV ONLY. WAAS CHANNEL # 48919 REFERENCE PATH ID: W09A CHART CIRCLING ICON. CHART KPMP. LTP HAE: -22 M							
ENVER (IF/IAF)		PADDS (FB)		090.68 / 6.14				2000									
PADDS (FAF)		TRUBE/3.00 NM TO RW09 (FB)		090.73 / 3.07													
TRUBE/3.00 NM TO RW09		RW09 (MAP) (FO)		090.73 / 3.00													
RW09 (MAP)		213 MSL		090.73				2000									
213 MSL		FORSU (FO)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W ENVER, LT, 090.68 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 090.73 FAF: PADDS DIST FAF TO MAP: 6.07 THLD: 6.07 4. MIN. ALT: ENVER 2000, PADDS 2000, TRUBE/3.00 NM TO RW09 1020* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2000 GS ALT AT: PADDS 2000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 55.4 34:1 IS CLEAR 8. MSA FROM: RW09 2600											MAG VAR: 7W EPOCH YEAR: 2015						
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD@					
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	213	1/2	200	213	1/2	200	213	1/2	200	213	1/2	200					
LNAV/VNAV DA	427	7/8	414	427	7/8	414	427	7/8	414	427	7/8	414					
LNAV MDA	480	1/2	467	480	1/2	467	480	1	467	480	1	467					
CIRCLING	520	1	507	620	1	607	780	2 1/4	767	780	2 1/2	767					
NOTES: CHART NOTE: RADAR REQUIRED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 4C (40F) OR ABOVE 54C (130F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FORT LAUDERDALE/HOLLYWOOD INTL (SEE FORM 8260-10)																	
CITY AND STATE				ELEVATION: 13 TDZE: 13				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP: RNAV (GPS) RWY 8	
FORT LAUDERDALE, FL				AIRPORT NAME:								RNAV (GPS) RWY 9, AMDT 2A				AMDT: 2	
				FORT LAUDERDALE EXECUTIVE								5 FEBRUARY 2015				DATED 09/18/2014	



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALTIMETER SETTING AND INCREASE LPV DA TO 231; LNAV/VNAV DA TO 445. INCREASE ALL MDA 20 FEET, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING FORT LAUDERDALE/HOLLYWOOD INTL ALTIMETER SETTING.

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT ENVER ON V267-437 SOUTHEAST BOUND



CITY AND STATE FORT LAUDERDALE, FL	ELEVATION: 13 TDZE: 13 AIRPORT NAME: FORT LAUDERDALE EXECUTIVE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 2A 5 FEBRUARY 2015	SUP: RNAV (GPS) RWY 8
				AMDT: 2
				DATED: 09/18/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFXE
RUNWAY	RW09
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W09A
LTP/FTP LATITUDE	261151.2680N
LTP/FTP LONGITUDE	0801051.1155W
LTP/FTP ELLIPSOIDAL HEIGHT	-00220
FPAP LATITUDE	261200.9400N
FPAP LONGITUDE	0800912.6400W
THRESHOLD CROSSING HEIGHT (TCH)	00055.4
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0920
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 A106A8A3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00036
FPAP ORTHOMETRIC HEIGHT	+00036

QUALITY
24
CHECKED

CITY AND STATE FORT LAUDERDALE, FL	ELEVATION: 13 AIRPORT NAME: FORT LAUDERDALE EXECUTIVE	TDZE: 13	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 2A 5 FEBRUARY 2015	SUP: RNAV (GPS) RWY 8
					AMDT: 2
					DATED: 09/18/2014

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KFXEK7FR09	AENVER	010ENVERK7EA0EE	AL	HF		09070040	+	02000	18000		A	JS
SUSAP	KFXEK7FR09	R	010ENVERK7EA0E	I	IF			+	02000	18000		A	JS
SUSAP	KFXEK7FR09	R	020PADDSK7EA1E	F	051TF		09070061	+	02000		RW09	K7PGA	JS
SUSAP	KFXEK7FR09	R	020PADDSK7EA2WALPV			ALNAV/VNAV							JS
SUSAP	KFXEK7FR09	R	021TRUBEK7EA0E	S	031TF		09070031	V	0102001030		-300		A JS
SUSAP	KFXEK7FR09	R	030RW09	K7PG0GY	M	031TF	09070030		00067		-300		A JS
SUSAP	KFXEK7FR09	R	040		0	M	0907	+	00213				A JS
SUSAP	KFXEK7FR09	R	050FORSUK7EA0EY		DF			+	02000				A JS
SUSAP	KFXEK7FR09	R	060FORSUK7EA0EE	R	HM		27090040	+	02000				A JS

[illegible][illegible][illegible]

QUALITY
24
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ENVER	ENVER	010	IAF	HF	L	FO		090.7 (083.7T)	004.0	AA 02000	
		ENVER	010	FACF	IF		FB				AA 02000	
		PADDS	020	FAF	TF		FB	0.5	090.7 (083.7T)	006.1	AA 02000	
		TRUBE	021	SDF	TF		FB	0.3	090.7 (083.7T)	003.1	AA 01020	GS 01030
		RW09	030	MAP	TF		FO	0.3	090.7 (083.7T)	003.0	AT 00067	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		090.7 (083.7T)		AA 00213	
		FORSU	050		DF		FO				AA 02000	
		FORSU	060		HM	R	FO		270.9 (263.9T)	004.0	AA 02000	
POINT DATA		WAYPOINT		LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS		
		ENVER		N261030.98		W0802420.77		N2610.516		W08024.346		
		FORSU		N261306.23		W0795802.55		N2613.104		W07958.043		
		PADDS		N261111.54		W0801733.58		N2611.192		W08017.560		
		TRUBE		N261131.67		W0801410.05		N2611.528		W08014.168		
		RW09		N261151.27		W0801051.12		N2611.855		W08010.852		
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW09	00012		55							



CITY AND STATE FORT LAUDERDALE, FL	ELEVATION: 13	TDZE: 13	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 8
	AIRPORT NAME: FORT LAUDERDALE EXECUTIVE		RNAV	RNAV (GPS) RWY 9, AMDT 2A	AMDT: 2
				5 FEBRUARY 2015	DATED: 09/18/2014