

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION LOC STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: 4.73 NM AFTER WZARD/I-FWA 5.24 DME/RADAR OR AT NUYIC/I-FWA 0.51 DME FIX					
FWA VORTAC		WZARD/I-FWA 5.24 DME/RADAR			321.77 / 6.51			2700		CLIMB TO 4000 ON I-FWA SE COURSE THEN RIGHT TURN DIRECT FWA VORTAC AND HOLD.					
OYIDU/FWA 16.00 DME CW (IAF)		ZOGOR/I-FWA 14.73 DME/RADAR (NOPT)			16.00 DME ARC (FWA LR-314)			2600							
ZOGOR/I-FWA 14.73 DME/RADAR (IF)		WZARD/I-FWA 5.24 DME/RADAR			140.75 / 9.49 (I-FWA)			2600							
										ADDITIONAL FLIGHT DATA: HOLD SE, RT, 320.75 INBOUND. FAS OBST: 1069 AAO 410345N/0851654W CHART VDP AT 1.31 DME DISTANCE VDP TO THLD 1.46 NM. CHART FWA R-285 AT OYIDU. CHART 2700 PRIOR TO WZARD IN PROFILE. WZARD TO RW14: 3.05/53 CHART: ASR CHART CIRCLING ICON.					
1. PT <u>L</u> SIDE OF COURSE <u>320.75</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>WZARD</u> (IAF)										MAG VAR: 6W EPOCH YEAR: 2020					
2.															
3. FAC <u>140.75</u> FAF <u>WZARD/I-FWA 5.24 DME/RADAR</u> DIST FAF TO MAP <u>4.73</u> THLD <u>5.40</u>															
4. MIN. ALT <u>WZARD 2600</u>															
8. MSA FROM: <u>FWA VORTAC 2700</u>															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-14	1320	1	518	1320	1	518	1320	1 3/8	518	1320	1 3/8	518	1320	1 3/8	518
CIRCLING	1320	1	505	1320	1	505	1420	1 3/4	606	1520	2 1/4	705	1520	2 1/2	705
NOTES:															
CHART NOTE: DME OR RADAR REQUIRED. @ CAT D 800-2 1/4, CAT E 800-2 1/2															
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON FWA VORTAC AIRWAY RADIALS 285 CW 335.															
CHART PROFILE NOTE: DISREGARD GS INDICATIONS.															
CHART PLANVIEW NOTE: DME OR RADAR REQUIRED.															
(CONTINUED ON PAGE 2)															
CITY AND STATE FORT WAYNE, IN		ELEVATION: 815 TDZE: 802 AIRPORT NAME: FORT WAYNE INTL		FACILITY IDENTIFIER: I-FWA		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC BC RWY 14, AMDT 15C, 04/27/2017				SUP AMDT DATE		10 15B 04/30/2015			

**LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART PLANVIEW NOTE: CAT E PROCEDURE TURN NA.****CHART PROFILE NOTE: USE I-FWA DME WHEN ON THE LOCALIZER COURSE.**

CITY AND STATE

FORT WAYNE, IN

ELEVATION: 815**TDZE: 802**

AIRPORT NAME:

FORT WAYNE INTL

FACILITY
IDENTIFIER:
I-FWAPROCEDURE NO./AMDT NO./EFFECTIVE DATE:
LOC BC RWY 14, AMDT 15C, 04/27/2017

SUP:

AMDT: **15B**DATED: **04/30/2015**