# U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

# TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and attitudes are in feet, MSL. Attitudes are minimum attitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

#### (1) TAKEOFF MINIMUMS:

RWY 7, 200-1 OR STANDARD WITH MINIMUM CLIMB OF 310 FEET PER NM TO 1000. RWY 25, 200-1 OR STANDARD WITH MINIMUM CLIMB OF 360 FEET PER NM TO 1000.

#### (2) TEXTUAL DEPARTURE PROCEDURE:

## (3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 7, TREES BEGINNING 4439' FROM DER, 1034' LEFT OF CENTERLINE, UP TO 100' AGL/933' MSL. TREES BEGINNING 2869' FROM DER, 1171' RIGHT OF CENTERLINE, UP TO 100' AGL/879' MSL. VEHICLE ABEAM DER 451' LEFT OF CENTERLINE, 17' AGL/796' MSL. NOTE: RWY 25, TREES BEGINNING 3371' FROM DER, 425' LEFT OF CENTERLINE, UP TO 100' AGL/925' MSL. TREES BEGINNING 1221' FROM DER,

624' RIGHT OF CENTERLINE, UP TO 100' AGL/999' MSL.



## (4) CONTROLLING OBSTACLES:

RWY 7: 933 TREE 391327.44N-0821232.03W. RWY 25: 919 TREE 391202.65N-0821446.27W.



(5) City, State

**ALBANY (ATHENS), OHIO** 

(6) Airport

**OHIO UNIVERSITY SNYDER FIELD** 

(7) Effective Date 11 FEB 2010 (8) Amdt. No. ORIG