

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
OCOQY (IF/IAF)	FOYGU (FB)	050.23 / 5.12	2600	LPV: DA LNAV/VNAV: DA LNAV: RW05
FOYGU (FAF)	RW05 (MAP) (FO)	050.28 / 4.88		
RW05 (MAP)	1265 MSL		3300	CLIMB TO 3300 DIRECT DEZLY AND HOLD.
1265 MSL	DEZLY (FO)			ADDITIONAL FLIGHT DATA: HOLD NE, RT, 230.42 INBOUND. CHART FAS OBST: 1170 TOWER 341135N/0861828W DISTANCE TO THLD FROM 250 HAT: 0.69 NM. CHART VDP AT 1.17 MILES TO RW05* *LNAV ONLY. WAAS CHANNEL # 93737 REFERENCE PATH ID: W05A CHART CIRCLING ICON. LTP HAE: 276.5 M

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD SW OCOQY, LT, 050.23 INBOUND, 3200 FT. IN LIEU OF PT (IAF)
3. FAC: 050.28 FAF: FOYGU DIST FAF TO MAP: 4.88 THLD: 4.88
4. MIN. ALT: OCOQY 3200, FOYGU 2600
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 2600 GS ALT AT: FOYGU 2600 OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 42.0 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 2W EPOCH YEAR: 1995

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1265	7/8	250	1265	7/8	250	1265	7/8	250	1265	7/8	250			
LNAV/VNAV DA	1332	1 1/8	317	1332	1 1/8	317	1332	1 1/8	317	1332	1 1/8	317			
LNAV MDA	1420	1	405	1420	1	405	1420	1 1/8	405	1420	1 1/8	405			
CIRCLING	1480	1	448	1500	1	468	1500	1 1/2	468	1680	2	648			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HUNTSVILLE INTL-ALBERT T. JONES FIELD ALTIMETER SETTING AND INCREASE ALL DA 139 FT AND ALL MDA 140 FT; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/2 MILE. INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE ALBERTVILLE, AL	ELEVATION: 1032 TDZE: 1015 AIRPORT NAME: ALBERTVILLE RGNL-THOMAS J BRUMLIK FLD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5, AMDT 1 2 APRIL 2015	SUP: AMDT: ORIG DATED 10/05/2000
-----------------------------------	--	------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
 AND CAT D 1/2 MILE.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F)
 CHART NOTE: BARO-VNAV AND VDP NA WHEN USING HUNTSVILLE INTL-ALBERT T. JONES FIELD ALTIMETER SETTING.
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA	FROM	TO	ALT
1.	320/30 CW 140/30 (NOPT)	320/15 CW 140/15	4000
2.	320/15 CW 140/15	OCOQY (IF/IAF) (FB)	3200
3.	140/30 CW 320/30	140/15 CW 320/15	4000
4.	140/15 CW 320/15	OCOQY (IF/IAF) (FO)	3200



CITY AND STATE ALBERTVILLE, AL	ELEVATION: 1032 TDZE: 1015 AIRPORT NAME: ALBERTVILLE RGNL-THOMAS J BRUMLIK FLD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5, AMDT 1 2 APRIL 2015	SUP:
				AMDT: ORIG
				DATED: 10/05/2000

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	8A0
RUNWAY	RW05
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W05A
LTP/FTP LATITUDE	341324.6865N
LTP/FTP LONGITUDE	0861547.9110W
LTP/FTP ELLIPSOIDAL HEIGHT	+02765
FPAP LATITUDE	341424.0315N
FPAP LONGITUDE	0861427.6435W
THRESHOLD CROSSING HEIGHT (TCH)	00042.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0888
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER E68BAFC8

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+03056
FPAP ORTHOMETRIC HEIGHT	+03056



CITY AND STATE ALBERTVILLE, AL	ELEVATION: 1032	TDZE: 1015	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5, AMDT 1 2 APRIL 2015	SUP:
	AIRPORT NAME: ALBERTVILLE RGNL-THOMAS J BRUMLIK FLD				AMDT: ORIG
					DATED: 10/05/2000

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	OCOQY	OCOQY	010	IAF	HF	L	FO		050.2 (048.2T)	004.0	AA 03200	
		OCOQY	010	FACF	IF		FB				AA 03200	
		FOYGU	020	FAF	TF		FB	0.5	050.2 (048.2T)	005.1	AA 02600	
		RW05	030	MAP	TF		FO	0.3	050.3 (048.3T)	004.9	AT 01045	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		050.3 (048.3T)		AA 01265	
	DEZLY	050		DF		FO				AA 03300	
	DEZLY	060		HM	R	FO		230.4 (228.4T)	004.0	AA 03300	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DEZLY	N342126.05	W0860455.33	N3421.434	W08604.922
	FOYGU	N341009.43	W0862011.65	N3410.157	W08620.194
	OCOQY	N340644.65	W0862447.63	N3406.744	W08624.794
	RW05	N341324.69	W0861547.91	N3413.412	W08615.799

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW05	01003	42



CITY AND STATE ALBERTVILLE, AL	ELEVATION: 1032	TDZE: 1015	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: ALBERTVILLE RGNL-THOMAS J BRUMLIK	FLD	RNAV	RNAV (GPS) RWY 5, AMDT 1 2 APRIL 2015	AMDT: ORIG
					DATED: 10/05/2000