

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 18, 36, NA - ENVIRONMENTAL

RWY 27, STANDARD

RWY 9, STANDARD WITH MINIMUM CLIMB OF 260 FT PER NM TO 600, OR 500-2 3/4 WITH MINIMUM CLIMB OF 210 FT PER NM TO 900, OR 900-2 1/2 FOR CLIMB IN VISUAL CONDITIONS.

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 9 - CLIMB HEADING 096 TO 700 BEFORE TURNING RIGHT, OR FOR CLIMB IN VISUAL CONDITIONS CROSS CRYSTAL RIVER AIRPORT AT OR ABOVE 800 BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 9, VEHICLES ON ROAD BEGINNING 6' FROM DER, FROM LEFT TO RIGHT OF CENTERLINE, UP TO 15' AGL/24' MSL. MULTIPLE TREES BEGINNING 364' FROM DER, FROM 680' LEFT OF CENTERLINE TO 820' RIGHT OF CENTERLINE, UP TO 100' AGL/129' MSL.

NOTE: RWY 27, TREES 17' FROM DER, 484' RIGHT OF CENTERLINE, UP TO 100' AGL/109' MSL. VEHICLES ON ROAD BEGINNING 368' FROM DER, FROM LEFT TO RIGHT OF CENTERLINE, UP TO 15' AGL/24' MSL. POWER LINE BEGINNING 474' FROM DER, FROM LEFT TO RIGHT OF CENTERLINE, UP TO 26' AGL/45' MSL. BUILDING 916' FROM DER, ON CENTERLINE, 26' AGL/35' MSL. MULTIPLE TREES BEGINNING 762' FROM DER, FROM 915' LEFT OF CENTERLINE TO 641' RIGHT OF CENTERLINE, UP TO 100' AGL/119' MSL.

(4) CONTROLLING OBSTACLES:

RWY 9: 370 MSL TOWER 285236.00N-0823125.00W, 658 MSL TOWER 285245.40N-0822915.60W

VCOA: 370 MSL TOWER 285236.00N-0823125.00W, 564 MSL TOWER 285030.00N-0823020.00W

(5) City, State

CRYSTAL RIVER, FL

(6) Airport

CRYSTAL RIVER

(7) Effective Date

08 APR 2010

(8) Amdt. No.

ORIG

