

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW34 CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 2000 DIRECT SAVOY AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 266 TREE 480934N/1220905W DISTANCE TO THLD FROM 200 HATH: 0.48 NM. CHART VDP AT 1.09 MILES TO RW34* *LNAV ONLY. WAAS CHANNEL # 90324 REFERENCE PATH ID: W34A LTP HAE: 16.1 M											
PAE VOR/DME (IAF)	SAVOY (NOPT) (FB)	039.58 / 6.08	2000												
SAVOY (IF/IAF)	YAYKU (FB)	342.10 / 5.97	1700												
YAYKU (FAF)	WIGIB/1.60 NM TO RW34 (FB)	342.10 / 3.19													
WIGIB/1.60 NM TO RW34	RW34 (MAP) (FO)	342.10 / 1.60	1000												
RW34 (MAP)	1000 MSL	342.10	2000												
1000 MSL	SAVOY (FO)														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 17E EPOCH YEAR: 2010											
2. HOLD S SAVOY, LT, 342.10 INBOUND, 2000 FT. IN LIEU OF PT (IAF)															
3. FAC: 342.10 FAF: YAYKU DIST FAF TO MAP: 4.79 THLD: 4.79															
4. MIN. ALT: SAVOY 2000, YAYKU 1700, WIGIB/1.60 NM TO RW34 680*															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: 1700 GS ALT AT: YAYKU 1700 OM: MM: IM:															
7. GS ANGLE: 3.00 TCH: 46.0 34:1 IS CLEAR															
8. MSA FROM: RW34 8100															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	328	3/4	200	328	3/4	200	328	3/4	200	328	3/4	200			
LNAV/VNAV DA	503	1	375	503	1	375	503	1	375	503	1	375			
LNAV MDA	520	3/4	392	520	3/4	392	520	7/8	392	520	7/8	392			
CIRCLING	800	1	663	860	1	723	860	2	723	920	2 1/2	783			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 43C (109F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON PAE VOR/DME AIRWAY RADIALS 298 CW 329. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WHIDBEY ISLAND NAS (AULT FIELD) (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 137 THRE: 128		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		QUALITY 3 CHECKED			
ARLINGTON, WA		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 34, ORIG				AMDT: NONE					
		ARLINGTON MUNI				25 AUG 2011				DATED					

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALTIMETER SETTING AND INCREASE ALL DA 66 FEET AND ALL MDA 80 FEET AND INCREASE LNAV/VNAV ALL CATS, AND LNAV AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE.

CHART NOTE: FOR INOPERATIVE MALS, INCREASE LNAV/VNAV CAT D VISIBILITY TO 1 1/4 AND INCREASE LNAV CAT D VISIBILITY TO 1 1/8.

CHART NOTE: FOR INOPERATIVE MALS WHEN USING WHIDBEY ISLAND NAS (AULT FIELD) ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 7/8, INCREASE LNAV/VNAV CAT D VISIBILITY TO 1 1/2, AND INCREASE LNAV CAT D VISIBILITY TO 1 3/8.

CHART NOTE: BARO-VNAV AND VDP NA WITH WHIDBEY ISLAND NAS (AULT FIELD) ALTIMETER SETTING.

QUALITY
3
CHECKED

CITY AND STATE

ARLINGTON, WA

ELEVATION: 137

THRE: 128

AIRPORT NAME:

ARLINGTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 34, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KAWO
RUNWAY RW34
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W34A
LTP/FTP LATITUDE 480917.0340N
LTP/FTP LONGITUDE 1220922.2570W
LTP/FTP ELLIPSOIDAL HEIGHT +00161
FPAP LATITUDE 481046.0600N
FPAP LONGITUDE 1220924.3500W
THRESHOLD CROSSING HEIGHT (TCH) 00046.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1128
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 35.0

CRC REMAINDER

F29CA76D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K1
LTP ORTHOMETRIC HEIGHT +00389
FPAP ORTHOMETRIC HEIGHT +00389

QUALITY
6
CHECKED

CITY AND STATE ARLINGTON, WA	ELEVATION: 137	THRE: 128	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 25 AUG 2011	SUP:
	AIRPORT NAME:				AMDT: NONE
	ARLINGTON MUNI				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
6
CHECKED

CITY AND STATE ARLINGTON, WA	ELEVATION: 137	THRE: 128	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 25 AUG 2011	SUP:	
	AIRPORT NAME:				AMDT:	NONE
	ARLINGTON MUNI				DATED:	

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
6
CHECKED

ELEVATION: 137 THRE: 128
AIRPORT NAME:
 ARLINGTON MUNI

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 34, ORIG
25 AUG 2011

SUP:	
AMDT:	NONE
DATED:	