

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 4.72 MILES AFTER WATON LOM	
PAE VOR/DME (IAF)	SAVOY INT (NOPT)	036.58 / 6.08	2000	CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 2000 DIRECT AW LOM AND HOLD.	
SAVOY INT (IF)	WATON LOM	342.10 / 6.04	1700		
				ADDITIONAL FLIGHT DATA: HOLD S, LT, 342.10 INBOUND. CHART FAS OBST: 550 TREE 480856N/1220714W AW LOM TO RW34: 3.05/46. CHART MAXIMUM 6,000 AT AW LOM.	

1. PT R SIDE OF COURSE 162.10 OUTBOUND 2000 FT WITHIN 10 MILES OF WATON LOM (IAF)
2. \_\_\_\_\_
3. FAC 342.10 FAF WATON LOM DIST FAF TO MAP 4.72 THLD 4.72
4. MIN. ALT AW LOM 1700
8. MSA FROM: AW LOM 150-305 2100, 305-150 8100

MAG VAR: 17E EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A X							
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-34	860	3/4	732	860	3/4	732	860	1 3/4	732	860	1 3/4	732			
CIRCLING	860	1	723	860	1	723	860	2	723	920	2 1/2	783			

**NOTES:**  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WHIDBEY ISLAND NAS (AULT FIELD) ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND INCREASE S-34 CATS B, C, AND D VISIBILITY 1/4 MILE AND INCREASE CIRCLING CAT B AND D VISIBILITY 1/4 MILE AND CAT C VISIBILITY 1/2 MILE.  
 CHART NOTE: FOR INOPERATIVE MALS, INCREASE S-34 CAT D VISIBILITY TO 2.  
 (SEE FORM 8260-10)

CITY AND STATE ARLINGTON, WA	ELEVATION: 137 THRE: 128 AIRPORT NAME: ARLINGTON MUNI	FACILITY IDENTIFIER: AW	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 34, AMDT 4 <b>25 AUG 2011</b>	SUP NDB OR GPS RWY 34 AMDT 3A DATE 12/20/2000
---------------------------------	----------------------------------------------------------------	----------------------------	------------------------------------------------------------------------------------	--------------------------------------------------------



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALS WHEN USING WHIDBEY ISLAND NAS (AULT FIELD) ALTIMETER SETTING,  
INCREASE S-34 CATS C AND D VISIBILITY TO 2 1/2.



CITY AND STATE ARLINGTON, WA	ELEVATION: 137      THRE: 128 AIRPORT NAME: ARLINGTON MUNI	FACILITY IDENTIFIER: AW	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 34, AMDT 4 <b>25 AUG 2011</b>	SUP: NDB OR GPS RWY 34
				AMDT: 3A
				DATED: 12/20/2000