

U.S. DEPARTMENT of TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in

COORDINATED

ATA
☒

AAT
☐

ALPA
☐

APA
☒

AOPA
☒

NBAA
☒

OTHER (specify)
☒

MDT APCH CTL, KN94 AMGR

TAKEOFF MINIMUMS:

RWY 8: STANDARD

RWY 24: 700-1 OR STANDARD WITH MINIMUM CLIMB OF 220' PER NM TO 1400.

IFR DEPARTURE PROCEDURE:

RWY 6/24: CLIMBING LEFT TURN TO 4000 OUTBOUND VIA
HGR VOR R-037 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLES:

RWY 24: 1238 ANTENNA: 395542/774144

DEPARTURE OBSTACLES:

RESTRICTED ARE R-5801

DEVELOPED BY		APPROVED BY	
SIGNATURE: <i>Richard K. Clark</i>	DATE: 05/28/98	SIGNATURE: <i>Bradley W. Rush</i>	DATE: OCT 1 1998
RICHARD K. CLARK	FIFO: AVN-110	BRADLEY W. RUSH	FIFO: AVN-110
CITY AND STATE	AIRPORT	EFFECTIVE	AMDT. NO.
CHAMBERSBURG, PA	CHAMBERSBURG MUNI	28 JAN 99	3

TL-98-25