

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH								
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW25								
IMNEH (IAF)		OKLUH (NOPT) (TF) (FB) (RNP 1.00)			336.22 / 10.00			5600		CLIMB TO 5000 DIRECT TILYU AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000.								
TOFTS (IAF)		OKLUH (NOPT) (TF) (FB) (RNP 1.00)			156.19 / 10.00			5600										
OKLUH (IF/IAF)		ZETER (TF) (FB) (RNP 1.00)			246.26 / 5.21			4700										
ZETER		RABTE (TF) (FB) (RNP 1.00)			246.20 / 3.73			3700										
RABTE (FAF)		WEDNA/3.50 NM TO RW25 (TF) (FB) (RNP 0.30)			246.16 / 2.97					ADDITIONAL FLIGHT DATA: HOLD SW, RT, 065.93 INBOUND. 2628 AAO 364439N/0830554W 2038 AAO 364139N/0830845W DISTANCE TO THLD FROM 303 HAT: 0.71 NM. CHART VDP AT 2.18 NM TO RW25* *LNAV ONLY. WAAS CHANNEL # 82717 REFERENCE PATH ID: W25A CHART CIRCLING ICON. LTP HAE: 399.2 M								
(SEE FORM 8260-10)																		
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																		
2. HOLD NE OKLUH, LT, 246.24 INBOUND, 5600 FT. IN LIEU OF PT (IAF)																		
3. FAC: 246.16 FAF: RABTE DIST FAF TO MAP: 6.47 THLD: 6.47																		
4. MIN. ALT: OKLUH 5600, ZETER 4700, RABTE 3700, WEDNA/3.50 NM TO RW25 2580*																		
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																		
6. MIN GS INCPT: 3700 GS ALT AT: RABTE 3700 OM: _____ MM: _____ IM: _____																		
7. GS ANGLE: 3.25 TCH: 58.0 34:1 IS NOT CLEAR																		
8. MSA FROM: _____																		
MAG VAR: 6W EPOCH YEAR: 2005																		
MINIMUMS																		
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A							@	
CATEGORY ==>		A			B			C			D			E				
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA			
LPV DA	1714	1	303	1714	1	303	1714	1	303		NA							
LNAV/VNAV DA	2284	3	873	2284	3	873	2284	3	873		NA							
LNAV MDA	2220	1	809	2220	1 1/4	809	2220	2 1/2	809		NA							
CIRCLING	2220	1	809	2220	1	809	2600	3	1189		NA							
NOTES: CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).																		
@ NA WHEN LOCAL WEATHER NOT AVAILABLE. @ CAT A, B 900-2, CAT C 1200-3																		
CITY AND STATE JONESVILLE, VA		ELEVATION: 1411 TDZE: 1411 AIRPORT NAME: LEE COUNTY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2 2 MARCH 2017					SUP: 4 AMDT: 1 DATED 09/23/2010						

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
WEDNA/3.50 NM TO RW25	RW25 (MAP) (TF) (FO) (RNP 0.30)	246.16 / 3.50	
RW25 (MAP)	1714 MSL	246.16	
1714 MSL	TILYU (DF) (FO) (RNP 1.00)		5000

TAA

	FROM	TO	ALT
1.	156/30 CW 336/30 (NOPT)	156/4 CW 336/4	6500
2.	156/4 CW 336/4	OKLUH (IF/IAF) (FB)	5600
3.	336/30 CW 066/30	IMNEH (IAF) (FB)	5600
4.	066/30 CW 156/30	TOFTS (IAF) (FB)	6200

CITY AND STATE
JONESVILLE, VA

ELEVATION: 1411 TDZE: 1411
 AIRPORT NAME:
LEE COUNTY

FACILITY
 IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 25, AMDT 2
 2 MARCH 2017

SUP: **4**
 AMDT: **CHECKED**
 DATED: **09/23/2010**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	0VG
RUNWAY	RW25
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W25A
LTP/FTP LATITUDE	363927.0385N
LTP/FTP LONGITUDE	0831237.6430W
LTP/FTP ELLIPSOIDAL HEIGHT	+03992
FPAP LATITUDE	363842.5400N
FPAP LONGITUDE	0831413.6140W
THRESHOLD CROSSING HEIGHT (TCH)	00058.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.25
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 74D1C886

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+04300
FPAP ORTHOMETRIC HEIGHT	+04300

CITY AND STATE

JONESVILLE, VA

ELEVATION: 1411

TDZE: 1411

AIRPORT NAME:

LEE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 25, AMDT 2

2 MARCH 2017

SUP:

QUALITY

4

AMDT:

CHECKED

DATED:

09/23/2010