

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM	TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW03 CLIMB TO 7500 THEN CLIMBING RIGHT TURN TO 9500 DIRECT TAWNE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 262.68 INBOUND. CHART FAS OBST: 7101 TREE 350747N/1114036W DISTANCE TO THLD FROM 250 HAT: 0.63 NM. CHART VDP AT 0.93 NM TO RW03* *LNAV ONLY. WAAS CHANNEL # 45718 REFERENCE PATH ID: W03A CHART CIRCLING ICON. LTP HAE: 2114.6 M						
FLG VOR/DME	SEZCY (TF) (FO) (RNP 2.00)			209.00 / 11.98			9900								
JUWSO (IAF)	SEZCY (NOPT) (TF) (FB) (RNP 1.00)			033.26 / 16.05			9600								
OATES (IAF)	SEZCY (NOPT) (TF) (FB) (RNP 1.00)			311.43 / 9.31			9600								
SEZCY (IF/IAF)	TOHQU (TF) (FB) (RNP 1.00)			031.09 / 5.96			8700								
TOHQU (FAF)	YEDUV/3.50 NM TO RW03 (TF) (FB) (RNP 0.30)			031.12 / 1.64											
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW SEZCY, RT, 031.09 INBOUND, 9600 FT. IN LIEU OF PT (IAF) 3. FAC: 031.12 FAF: TOHQU DIST FAF TO MAP: 5.14 THLD: 5.14 4. MIN. ALT: SEZCY 9600, TOHQU 8700, YEDUV/3.50 NM TO RW03 8160* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 8700 GS ALT AT: TOHQU 8700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: RW03 14100															
										MAG VAR: 10E			EPOCH YEAR: 2020		
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	7264	3/4	250	7264	3/4	250	7264	3/4	250	7264	3/4	250			
LNAV/VNAV DA	7282	7/8	268	7282	7/8	268	7282	7/8	268	7282	7/8	268			
LNAV MDA	7360	1	346	7360	1	346	7360	1	346	7360	1	346			
CIRCLING	7520	1	506	7560	1	546	8100	3	1086	8560	3	1546			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-2F) OR ABOVE 44C (112F). @ CAT C 1100-3, CAT D 1600-3 CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FLG VOR/DME ON V291 EAST BOUND															
CITY AND STATE		ELEVATION: 7014 TDZE: 7014			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:			
FLAGSTAFF, AZ		AIRPORT NAME:					RNAV (GPS) RWY 3, AMDT 1					AMDT: ORIG-A			
		FLAGSTAFF PULLIAM					7 DECEMBER 2017					DATED 05/02/2013			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
YEDUV/3.50 NM TO RW03	RW03 (MAP) (TF) (FO) (RNP 0.30)	031.12 / 3.50	
RW03 (MAP)	7500 MSL (CA)	031.12	7500
7500 MSL	TAWNE (DF) (FO) (RNP 1.00)		9500



CITY AND STATE FLAGSTAFF, AZ	ELEVATION: 7014	TDZE: 7014	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 7 DECEMBER 2017	SUP:
	AIRPORT NAME:				AMDT: ORIG-A
	FLAGSTAFF PULLIAM				DATED: 05/02/2013

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFLG
RUNWAY	RW03
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W03A
LTP/FTP LATITUDE	350752.3855N
LTP/FTP LONGITUDE	1114044.1275W
LTP/FTP ELLIPSOIDAL HEIGHT	+21146
FPAP LATITUDE	350859.5660N
FPAP LONGITUDE	1113932.6125W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 28E12EBA

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+21378
FPAP ORTHOMETRIC HEIGHT	+21378

QUALITY
16
CHECKED

CITY AND STATE FLAGSTAFF, AZ	ELEVATION: 7014 AIRPORT NAME: FLAGSTAFF PULLIAM	TDZE: 7014 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 7 DECEMBER 2017	SUP:
				AMDT: ORIG-A
				DATED: 05/02/2013