

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW12R CLIMB TO 1000 THEN CLIMBING RIGHT TURN TO 3500 DIRECT MARIC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 221.00 INBOUND. CHART FAS OBST: 668 T-L TWR 352727N/1190428W DISTANCE TO THLD FROM 250 HAT: 0.63 NM. CHART VDP AT 1.28 NM TO RW12R* *LNAV ONLY. WAAS CHANNEL # 61040 REFERENCE PATH ID: W12B CHART CIRCLING ICON. LTP HAE: 115.3 M					
MARIC		MOMUE (TF) (FO) (RNP 2.00)		349.27 / 20.96				3400							
EHF VORTAC		MOMUE (TF) (FO) (RNP 2.00)		296.30 / 9.50				3400							
COREZ (IAF)		MOMUE (NOPT) (TF) (FB) (RNP 1.00)		067.09 / 11.82				3400							
PONDD (IAF)		MOMUE (NOPT) (TF) (FB) (RNP 1.00)		161.45 / 14.24				3400							
MOMUE (IF/IAF) (SEE FORM 8260-10)		WENTI (TF) (FB) (RNP 1.00)		121.21 / 6.34				2500							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NW MOMUE, RT, 121.21 INBOUND, 3400 FT. IN LIEU OF PT (IAF) 3. FAC: 121.27 FAF: WENTI DIST FAF TO MAP: 6.16 THLD: 6.16 4. MIN. ALT: MOMUE 3400, WENTI 2500, TEDBE/2.90 NM TO RW12R 1440* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2500 GS ALT AT: WENTI 2500 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: RW0!! 8800										MAG VAR: 14E EPOCH YEAR: 1985					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD						
CATEGORY ==>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	738	3/4	250	738	3/4	250	738	3/4	250	738	3/4	250			
LNAV/VNAV DA	969	1 5/8	481	969	1 5/8	481	969	1 5/8	481	969	1 5/8	481			
LNAV MDA	920	1	432	920	1	432	920	1 1/4	432	920	1 1/4	432			
CIRCLING	960	1	450	960	1	450	960	1 1/2	450	1060	2	550			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -1C (31F) OR ABOVE 54C (130F). CHART NOTE: CIRCLING NA NE OF RWY 12L-30R. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EHF VORTAC ON V165 SOUTHBOUND.															
CITY AND STATE		ELEVATION: 510 TDZE: 488				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
BAKERSFIELD, CA		AIRPORT NAME: MEADOWS FIELD						RNAV (GPS) RWY 12R, ORIG 04/27/2017				AMDT: NONE			
												DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
WENTI (FAF)	TEDBE/2.90 NM TO RW12R (TF) (FB) (RNP 0.30)	121.27 / 3.26	
TEDBE/2.90 NM TO RW12R	RW12R (MAP) (TF) (FO) (RNP 0.30)	121.27 / 2.90	
RW12R (MAP)	1000 MSL (CA)	121.27	
1000 MSL	MARIC (DF) (FO) (RNP 1.00)		3500

QUALITY
16
CHECKED

CITY AND STATE BAKERSFIELD, CA	ELEVATION: 510 AIRPORT NAME: MEADOWS FIELD	TDZE: 488 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12R, ORIG 04/27/2017	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBFL
RUNWAY	RW12R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W12B
LTP/FTP LATITUDE	352619.4810N
LTP/FTP LONGITUDE	1190356.2705W
LTP/FTP ELLIPSOIDAL HEIGHT	+01153
FPAP LATITUDE	352516.0245N
FPAP LONGITUDE	1190239.6130W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0400
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 421520A0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+01486
FPAP ORTHOMETRIC HEIGHT	+01486

QUALITY
16
CHECKED

CITY AND STATE BAKERSFIELD, CA	ELEVATION: 510 AIRPORT NAME: MEADOWS FIELD	TDZE: 488 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12R, ORIG 04/27/2017	SUP:
				AMDT: NONE
				DATED: