

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW34 CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 3000 DIRECT JUSPO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 217 TREE 364057N/0772909W DISTANCE TO THLD FROM 250 HAT: 0.69 NM. CHART VDP AT 1.03 NM TO RW34* *LNAV ONLY. WAAS CHANNEL # 63226 REFERENCE PATH ID: W34A CHART CIRCLING ICON. LTP HAE: -.3 M						
HORAN (IAF)		JUSPO (NOPT) (TF) (FB) (RNP 1.00)			245.56 / 7.65			2000								
RETE (IAF)		JUSPO (NOPT) (TF) (FB) (RNP 1.00)			065.40 / 7.65			2000								
JUSPO (IF/IAF)		IQJAZ (TF) (FB) (RNP 1.00)			335.48 / 6.01			1600								
IQJAZ (FAF)		SIPLE/1.80 NM TO RW34 (TF) (FB) (RNP 0.30)			335.43 / 2.75											
SIPLE/1.80 NM TO RW34		RW34 (MAP) (TF) (FO) (RNP 0.30)			335.43 / 1.80											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE JUSPO, RT, 335.48 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 335.43 FAF: IQJAZ DIST FAF TO MAP: 4.55 THLD: 4.55 4. MIN. ALT: JUSPO 2000, IQJAZ 1600, SIPLE/1.80 NM TO RW34 720* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: IQJAZ 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 42.5 34:1 IS CLEAR 8. MSA FROM: RW34 1900																
										MAG VAR: 10W EPOCH YEAR: 2000						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD						
CATEGORY >>>>>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	372	1	250	372	1	250		NA			NA					
LNAV/VNAV DA	372	1	250	372	1	250		NA			NA					
LNAV MDA	480	1	358	480	1	358		NA			NA					
CIRCLING	580	1	453	580	1	453	680	1 1/2	553		NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA.																
CITY AND STATE		ELEVATION: 127 TDZE: 122			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:				
EMPORIA, VA		AIRPORT NAME: EMPORIA-GREENSVILLE RGNL						RNAV (GPS) RWY 34, AMDT 2 22 JUNE 2017				AMDT: 1A				
												DATED 04/03/2014				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW34 (MAP)	600 MSL (CA)	335.43	600
600 MSL	JUSPO (DF) (FO) (RNP 1.00)		3000

QUALITY
24
CHECKED

CITY AND STATE
EMPORIA, VA

ELEVATION: 127 TDZE: 122
AIRPORT NAME:
EMPORIA-GREENSVILLE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 34, AMDT 2
22 JUNE 2017

SUP:
AMDT: 1A
DATED: 04/03/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KEMV
RUNWAY	RW34
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W34A
LTP/FTP LATITUDE	364052.3045N
LTP/FTP LONGITUDE	0772840.4330W
LTP/FTP ELLIPSOIDAL HEIGHT	-00003
FPAP LATITUDE	364205.7370N
FPAP LONGITUDE	0772943.3530W
THRESHOLD CROSSING HEIGHT (TCH)	00042.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 D26C8824

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+00335
FPAP ORTHOMETRIC HEIGHT	+00335

QUALITY
24
CHECKED

CITY AND STATE EMPORIA, VA	ELEVATION: 127 AIRPORT NAME: EMPORIA-GREENSVILLE RGNL	TDZE: 122 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, AMDT 2 22 JUNE 2017	SUP:
				AMDT: 1A
				DATED: 04/03/2014