

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES										MISSED APPROACH							
FROM			TO			COURSE AND DISTANCE			ALTITUDE								
OBH VORTAC (IAF)			ZAMOG (NOPT) (FB)			110.68 / 11.55			4000		LPV: DA LNAV/VNAV: DA LNAV: RW16						
HUDNI (IAF)			ZAMOG (NOPT) (FB)			225.93 / 10.98			4000		CLIMB TO 4000 DIRECT HOMKI AND HOLD.						
ZAMOG (IF/IAF)			WOMAM (FB)			158.20 / 6.15			3300								
WOMAM (FAF)			OMEYY/1.60 NM TO RW16 (FB)			158.21 / 3.25					ADDITIONAL FLIGHT DATA: HOLD S, RT, 338.29 INBOUND. CHART FAS OBST: 1774 TREE 410825N/0980434W DISTANCE TO THLD FROM 293 HATH: 0.79 NM. WAAS CHANNEL # 82220 REFERENCE PATH ID: W16A LTP HAE: 497.6 M						
OMEYY/1.60 NM TO RW16			RW16 (MAP) (FO)			158.22 / 1.60											
RW16 (MAP)			2008 MSL			158.22			4000								
2008 MSL			HOMKI (FO)														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)																	
2. <u>HOLD N ZAMOG, RT, 158.20 INBOUND, 4000 FT. IN LIEU OF PT (IAF)</u>																	
3. FAC: <u>158.21</u> FAF: <u>WOMAM</u> DIST FAF TO MAP: <u>4.85</u> THLD: <u>4.85</u>																	
4. MIN. ALT: <u>ZAMOG 4000, WOMAM 3300, OMEYY/1.60 NM TO RW16 2260*</u>																	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>																	
6. MIN GS INCPT: <u>3300</u> GS ALT AT: <u>WOMAM 3300</u> OM: <u> </u> MM: <u> </u> IM: <u> </u>																	
7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR																	
8. MSA FROM: <u>RW16 4100</u>																	
										MAG VAR: 5E			EPOCH YEAR: 2010				
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT																	
ALTERNATE: N A X																	
CATEGORY >>>>>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	2008	1	293	2008	1	293		NA			NA						
LNAV/VNAV DA	2008	1	293	2008	1	293		NA			NA						
LNAV MDA	2080	1	365	2080	1	365		NA			NA						
CIRCLING	2140	1	423	2180	1	463		NA			NA						
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: USE AURORA ALTIMETER SETTING; WHEN NOT RECEIVED, USE GRAND ISLAND ALTIMETER SETTING AND INCREASE ALL DA 9 FT AND ALL MDA 20 FT. (SEE FORM 8260-10)																	
CITY AND STATE				ELEVATION: 1717 THRE: 1715				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:	
CENTRAL CITY, NE				AIRPORT NAME:								RNAV (GPS) RWY 16, ORIG				AMDT: NONE	
				CENTRAL CITY MUNI-LARRY REINEKE FIELD								30 JUN 2011				DATED	

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: BARO-VNAV NA.

***LNAV ONLY**

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIALS ON OBH VORTAC AIRWAY RADIALS 041 CW 169.

QUALITY
2
CHECKED

CITY AND STATE
CENTRAL CITY, NE

ELEVATION: 1717 THRE: 1715
AIRPORT NAME:
CENTRAL CITY MUNI-LARRY REINEKE FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, ORIG
30 JUN 2011

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	07K
RUNWAY	RW16
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W16A
REFERENCE PATH IDENTIFIER (APPROACH ID)	410659.1215N
LTP/FTP LATITUDE	0980311.7780W
LTP/FTP LONGITUDE	+04976
LTP/FTP ELLIPSOIDAL HEIGHT	410533.7600N
FPAP LATITUDE	0980237.7800W
FPAP LONGITUDE	00040.0
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	1624
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	50.0
VERTICAL ALERT LIMIT (VAL)	

CRC REMAINDER

5FF3F06A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+05228
FPAP ORTHOMETRIC HEIGHT	+05228

QUALITY
2
CHECKED

CITY AND STATE
CENTRAL CITY, NE

ELEVATION: 1717 THRE: 1715
AIRPORT NAME:
CENTRAL CITY MUNI-LARRY REINEKE FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, ORIG
30 JUN 2011

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
6
CHECK

CITY AND STATE CENTRAL CITY, NE	ELEVATION: 1717	THRE: 1715	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 16, ORIG	AMDT: NONE
	CENTRAL CITY MUNI-LARRY REINEKE FIELD			30 JUN 2011	DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP 07K K3GRW16 0037001582 N41065912W098031178+0000 +0497601715000040060R

SUSAP 07K K3PR16 RW16 001 0000W16A0N4106591215W09803117780+049760300N4105337600W09802377800106751624000400F4005005FF3F06A
SUSAP 07K K3PR16 RW16 002E +05228+05228LPV 82220

SUSAP 07K K3SRW16 K3PG	0	18018004125	M
------------------------	---	-------------	---

QUALITY
6
CHECKED

ELEVATION: 1717 THRE: 1715
AIRPORT NAME:
CENTRAL CITY MUNI-LARRY REINEKE FIELD

**FACILITY
IDENTIFIER:**
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, ORIG
30 JUN 2011

SUP:	
AMDT:	NONE
DATED:	