

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE				ALTITUDE		MAP: BEPME/EED 22.10 DME FIX								
EED VORTAC (IAF)		BORYU/EED 10.00 DME			334.59 / 10.00				5000		CLIMBING RIGHT TURN TO 6000 ON HEADING 120.00 AND EED VORTAC R-344 TO EED VORTAC AND HOLD.								
BORYU/EED 10.00 DME (IF)		AGGID/EED 16.00 DME			334.59 / 6.00 (EED R-335)				3100										
										ADDITIONAL FLIGHT DATA: HOLD SE, RT, 334.59 INBOUND. FAS OBST: 1680 AAO 350519N/1143027W CHART CIRCLING ICON. CHART TURTLE MOA. CHART ARRIVAL HOLDING AT EED VORTAC, HOLD SE, RT, 334.59 INBOUND 6000. AGGID TO RW34: 3.18/45									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 15E EPOCH YEAR:1965									
2. PROFILE STARTS AT EED VORTAC																			
3. FAC 334.59 FAF AGGID/EED 16.00 DME DIST FAF TO MAP _____ THLD 6.96																			
4. MIN. ALT EED VORTAC 6000, BORYU 5000, AGGID 3100																			
8. MSA FROM: EED VORTAC 070-160 6800, 160-250 5400, 250-340 5000, 340-070 8900																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: N A										@				
CATEGORY =====>		A			B			C			D			E					
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-34	2840	1 1/4	2133	2840	1 1/2	2133	2840	3	2133	2840	3	2133							
CIRCLING	2840	1 1/4	2133	2840	1 1/2	2133	2840	3	2133	2840	3	2133							
NOTES:																			
CHART NOTE: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. @ CAT A, B 2200-2, CAT C, D 2200-3																			
CHART NOTE: DME REQUIRED.																			
CHART NOTE: CIRCLING RWY 16 NA AT NIGHT.																			
CITY AND STATE BULLHEAD CITY, AZ		ELEVATION: 707 TDZE: 707 AIRPORT NAME: LAUGHLIN/BULLHEAD INTL		FACILITY IDENTIFIER: EED		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 34, AMDT 2, 03/02/2017					SUP VOR/DME RWY 34 AMDT DATE 07/02/2009								

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

BULLHEAD CITY, AZ

ELEVATION: 707

TDZE: 707

AIRPORT NAME:

LAUGHLIN/BULLHEAD INTL

FACILITY
IDENTIFIER:

EED

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 34, AMDT 2, 03/02/2017

SUP: VOR/DME RWY 34

AMDT: 1

DATED: 07/02/2009

QUALITY
4
CHECKED