

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: I-GSN 1.58 DME					
HIRCH/UNZ 100.00 DME		SN NDB		348.04 / 19.55				2600		CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 2800 DIRECT SN NDB AND HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 1600 ON HEADING 070 THEN CLIMBING RIGHT TURN TO 5000 ON HEADING 180 FOR RADAR VECTORS. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 246.00 INBOUND. CHART CIRCLING ICON. CHART VDP AT 2.25 DME * DISTANCE VDP TO THLD 0.67NM 305 AAO 150518N/1453830E CHART PLANVIEW NOTE: DME REQUIRED.					
SN NDB		KORDY/I-GSN 7.34 DME		245.81 / 5.28				2100							
WILLE/I-GSN 23.71 DME (IAF)		PONO/I-GSN 17.39 DME (NOPT)		065.80 / 6.32 (I-GSN)				2900							
PONO/I-GSN 17.39 DME (IF)		KORDY/I-GSN 7.34 DME		065.80 / 10.05 (I-GSN)				2100							
1. PT <u>L</u> SIDE OF COURSE <u>245.80</u> OUTBOUND <u>2100</u> FT WITHIN <u>10</u> MILES OF <u>KORDY</u> (IAF)										MAG VAR: 2E EPOCH YEAR: 1985					
2. _____															
3. FAC: <u>065.80</u> FAF: <u>KORDY/I-GSN 7.34 DME</u> DIST FAF TO MAP: _____ THLD: <u>5.76</u>															
4. MIN. ALT: <u>KORDY 2100, JIDSU/I-GSN 2.88 DME 660*</u>															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: <u>1020</u>															
6. MIN GS INCPT: <u>2100</u> GS ALT AT: <u>KORDY 2100</u> OM: _____ MM: _____ IM: _____															
7. GS ANGLE: <u>3.00</u> TCH: <u>55.3</u>															
8. MSA FROM: <u>SN NDB 2800</u>															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A X							
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 07	415	1/2	200	415	1/2	200	415	1/2	200	415	1/2	200			
S-LOC 07	480	1/2	265	480	1/2	265	480	1/2	265	480	1/2	265			
CIRCLING	720	1	505	720	1	505	720	1 1/2	505	780	2	565			
NOTES: CHART NOTE: CIRCLING NA NORTH OF RWY 6-24. *LOC ONLY CHART NOTE: ADF AND DME REQUIRED															
CITY AND STATE SAIPAN ISLAND, CQ		ELEVATION: 215 TDZE: 215 AIRPORT NAME: FRANCISCO C ADA/SAIPAN INTL		FACILITY IDENTIFIER: I-GSN		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 7, AMDT 6, 03/02/2017				SUP: ILS OR LOC/DME RWY 7 AMDT: 5E DATED 05/02/2013					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE SAIPAN ISLAND, CQ	ELEVATION: 215	TDZE: 215	FACILITY IDENTIFIER: I-GSN	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 7, AMDT 6, 03/02/2017	SUP: ILS OR LOC/DME RWY 7
	AIRPORT NAME: FRANCISCO C ADA/SAIPAN INTL	AMDT: 5E			
	DATED: 05/02/2013				