

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

TYPE: RNAV SID

DP ROUTE DESCRIPTION:

CHANDLER:

TAKEOFF RWY 4L: CLIMB HEADING 037.62 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 4R: CLIMB HEADING 037.63 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 22L: CLIMB HEADING 217.64 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 22R: CLIMB HEADING 217.63 OR AS ASSIGNED BY ATC, THENCE...

...EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

PHOENIX DEER VALLEY:

TAKEOFF RWY 25L: CLIMBING RIGHT TURN HEADING 320.00 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 25R: CLIMBING RIGHT TURN HEADING 320.00 OR AS ASSIGNED BY ATC, THENCE...

... EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

GLENDALE MUNI:

TAKEOFF RWY 1: CLIMB HEADING 013.71 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 19: CLIMB HEADING 200.00 OR AS ASSIGNED BY ATC, THENCE...

... EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

PHOENIX GOODYEAR:

TAKEOFF RWY 3: CLIMB HEADING 028.09 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 21: CLIMB HEADING 228.00 OR AS ASSIGNED BY ATC, THENCE...

... EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

PHOENIX-MESA GATEWAY:

TAKEOFF RWY 12L: CLIMB HEADING 123.57 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 12C: CLIMB HEADING 123.57 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 12R: CLIMB HEADING 123.56 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 30L: CLIMB HEADING 303.57 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 30C: CLIMB HEADING 303.58 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 30R: CLIMB HEADING 303.58 OR AS ASSIGNED BY ATC, THENCE...

...EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

PHOENIX SKY HARBOR INTL:

TAKEOFF RWY 7L: CLIMB HEADING 078.04 TO 1640, THEN DIRECT SPRKY, THEN LEFT TURN DIRECT TO CROSS GOALY AT/BELOW 9000, THEN ON TRACK 337.39 TO QUAKY, THENCE...

TAKEOFF RWY 7R: CLIMB HEADING 078.03 TO 1640, THEN DIRECT SPRKY, THEN LEFT TURN DIRECT TO CROSS GOALY AT/BELOW 9000, THEN ON TRACK 337.39 TO QUAKY, THENCE...

TAKEOFF RWY 8: CLIMB HEADING 078.06 TO 1640, THEN DIRECT SPRKY, THEN LEFT TURN DIRECT TO CROSS GOALY AT/BELOW 9000, THEN ON TRACK 337.39 TO QUAKY, THENCE...

TAKEOFF RWY 25L: CLIMB HEADING 258.05 TO INTERCEPT COURSE 307.50 TO TWSND, THEN ON TRACK 349.18 TO OXYGN, THEN ON TRACK 034.74 TO ZILUB, THEN ON TRACK 356.97 TO QUAKY, THENCE...

TAKEOFF RWY 25R: CLIMB HEADING 258.06 TO INTERCEPT COURSE 307.50 TO TWSND, THEN ON TRACK 349.18 TO OXYGN, THEN ON TRACK 034.74 TO ZILUB, THEN ON TRACK 356.97 TO QUAKY, THENCE...

TAKEOFF RWY 26: CLIMB HEADING 258.08 TO INTERCEPT COURSE 307.50 TO TWSND, THEN ON TRACK 349.18 TO OXYGN, THEN ON TRACK 034.74 TO ZILUB, THEN ON TRACK

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

356.97 TO QUAKY, THENCE...

...ON TRACK 342.77 TO SNOBL, THEN ON (TRANSITION). MAINTAIN 8000, EXPECT HIGHER ALTITUDE 3 MINUTES AFTER DEPARTURE.

SCOTTSDALE:

TAKEOFF RWY 3: CLIMBING LEFT TURN HEADING 335.00 OR AS ASSIGNED BY ATC, THENCE...

TAKEOFF RWY 21: CLIMBING RIGHT TURN HEADING 335.00 OR AS ASSIGNED BY ATC. THENCE...

... EXPECT RADAR VECTORS TO QUAKY, THEN ON TRACK 342.77 TO SNOBL. THEN ON (TRANSITION), EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes
CARTL	SNOBL4.CARTL	SNOBL	CARTL	TRACK 342.78	20.08	FL180	9300	
GRAND CANYON	SNOBL4.GCN	SNOBL	CARTL	TRACK 342.78	20.08	FL180	9300	
		CARTL	LOFTS	TRACK 342.70	35.95	FL180	11500	
		LOFTS	RIMMM	TRACK 343.35	10.19	FL180	11500	
		RIMMM	GCN VOR/DME	TRACK 342.42	25.80	FL180	9500	
JARPA	SNOBL4.JARPA	SNOBL	CARTL	TRACK 342.78	20.08	FL180	9300	
		CARTL	JARPA	TRACK 050.04	122.88	FL180	10700	
RIMMM	SNOBL4.RIMMM	SNOBL	CARTL	TRACK 342.78	20.08	FL180	9300	
		CARTL	LOFTS	TRACK 342.70	35.95	FL180	11500	
		LOFTS	RIMMM	TRACK 343.35	10.19	FL180	11500	
YOOPR	SNOBL4.YOOPR	SNOBL	CARTL	TRACK 342.78	20.08	FL180	9300	
		CARTL	YOOPR	TRACK 042.93	94.08	FL180	10700	

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RNAV 1.

NOTE: TURBOJETS AND TURBOPROPS ONLY.

NOTE: RADAR REQUIRED.

KCHD, KDVT, KGEU, KGYR, KIWA, KSDL NOTE: GPS REQUIRED.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

KPHX NOTE: DME/DME/IRU OR GPS REQUIRED.
 NOTE: JARPA TRANSITION ATC ASSIGNED ONLY.
 NOTE: YOOPR TRANSITION ATC ASSIGNED ONLY.
 NOTE: CARTL TRANSITION FOR FLG OR PGA TERMINAL ARRIVALS ONLY.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT USING JARPA TRANSITION, INW AND DRK DMES MUST BE OPERATIONAL.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT USING YOOPR TRANSITION, DRK DME MUST BE OPERATIONAL.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT DEPARTING KPHX, IWA DME MUST BE OPERATIONAL.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT DEPARTING KPHX RWYS 25L/R, 26, TFD AND BXK DMES MUST BE OPERATIONAL.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT DEPARTING KPHX RWYS 8, 25R, 26, DRK DME MUST BE OPERATIONAL.
 KPHX NOTE: FOR NON-GPS EQUIPPED AIRCRAFT DEPARTING KPHX RWYS 7L/R, PXR DME MUST BE OPERATIONAL.
 NOTE: AIRCRAFT DEPARTING KGEU AND KGYR ATC ASSIGNED ONLY

TAKEOFF MINIMUMS:
 CHANDLER:
 RWY 4L/R, 22L/R: STANDARD.

PHOENIX DEER VALLEY:
 RWY 7L/R: NA – OBSTACLES.
 RWY 25L/R: STANDARD WITH MINIMUM CLIMB OF 370 FT/NM TO 4600.

GLENDAL MUNI:
 RWY 1, 19: STANDARD.

PHOENIX GOODYEAR:
 RWY 3, 21: STANDARD.

PHOENIX-MESA GATEWAY:
 RWY 12L/C/R: STANDARD WITH A MINIMUM CLIMB OF 250 FT/NM TO 3100.
 RWY 30L/C/R: STANDARD.

PHOENIX SKY HARBOR INTL:
 RWY 7L/R: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1640, THEN MINIMUM CLIMB OF 230 FT/NM TO 10000.
 RWY 8: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1640, THEN MINIMUM CLIMB OF 300 FT/NM TO 10000.
 RWY 25L/R, 26: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 2140.

SCOTTSDALE:
 RWY 3: STANDARD WITH MINIMUM CLIMB OF 445 FT/NM TO 4600.
 RWY 21: STANDARD WITH MINIMUM CLIMB OF 300 FT/NM TO 4600.

TAKEOFF OBSTACLES NOTES:

CHANDLER:
 NOTE: RWY 4L, ANTENNA ON BUILDING 69 FT FROM DER, 515 FT LEFT OF CENTERLINE, 25 FT AGL/1281 FT MSL. TOWER 981 FT FROM DER. 615 FT LEFT OF CENTERLINE, 80 FT AGL/1319 FT MSL. TREES AND POLES BEGINNING 1100 FT FROM DER. 458 FT LEFT OF CENTERLINE, UP TO 30FT AGL/1272 FT MSL.
 NOTE: RWY 4R, POLES BEGINNING 1298 FT FROM DER. 56 FT LEFT OF CENTERLINE, UP TO 36 FT AGL/1283 FT MSL.
 NOTE: RWY 22L, TREE 336 FT FROM DER, 511 FT RIGHT OF CENTERLINE, 15 FT AGL/1250 FT MSL. TREE 988 FT FROM DER, 756 FT LEFT OF CENTERLINE, 30 FT AGL/1266 FT MSL. NOTE: RWY 22R, BUILDING 30 FT FROM DER, 441 FT RIGHT OF CENTERLINE, 24 FT AGL/1254 FT MSL. VEHICLES BEGINNING 199 FT FROM DER, 271 FT RIGHT OF CENTERLINE, 15 FT AGL/1246 FT MSL. POLES AND TREES BEGINNING 471 FT FROM DER, 45 FT LEFT OF CENTERLINE, UP TO 36 FT AGL/1290 FT MSL. TREES AND POLES BEGINNING 1088 FT FROM DER. 50FT RIGHT OF CENTERLINE, UP TO 36 FT AGL/1274 FT MSL.

QUALITY
3
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

PHOENIX DEER VALLEY:

NOTE: RWY 25L, POLE 1127 FT FROM DER, 498 FT RIGHT OF CENTERLINE, 36 FT AGL/1475 FT MSL. POLE 1184 FT FROM DER, 495 FT LEFT OF CENTERLINE, 32 FT AGL/1471 FT MSL.

NOTE: RWY 25R, MULTIPLE ANTENNAS BEGINNING 1.4 NM FROM DER, 1847 FT RIGHT OF CENTERLINE, UP TO 96 FT AGL/1806 FT MSL.

GLENDALDE MUNI:

NOTE: RWY 1, LIGHT ON BLAST FENCE 4 FT FROM DER, 130 FT LEFT OF CENTERLINE, UP TO 10 FT AGL/1088 FT MSL. TREES BEGINNING 124 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 30 FT AGL/1104 FT MSL. VEHICLES BEGINNING 299 FT FROM DER, 80 FT RIGHT OF CENTERLINE, UP TO 15 FT AGL/1091 FT MSL. POLES AND TREES BEGINNING 400 FT FROM DER, 197 FT RIGHT OF CENTERLINE, UP TO 75 FT AGL/1144 FT MSL.

NOTE: RWY 19, TREES BEGINNING 281 FT FROM DER, 331 FT LEFT OF CENTERLINE, UP TO 33 FT AGL/1060 FT MSL.

PHOENIX GOODYEAR:

NOTE: RWY 3, POLES BEGINNING 159 FT FROM DER, 267 FT RIGHT OF CENTERLINE, UP TO 47 FT AGL/1015 FT MSL. BLDG 1512 FT FROM DER, 828 FT RIGHT OF CENTERLINE, 48 FT AGL/1014 FT MSL. TREE 1957 FT FROM DER, 551 FT RIGHT OF CENTERLINE, UP TO 49 FT AGL/1019 FT MSL.

NOTE: RWY 21, TRANSMISSION TOWER 2610 FT FROM DER, 1078 FT LEFT OF CENTERLINE, 125 FT AGL/1047 FT MSL. TRANSMISSION TOWER 3190 FT FROM DER, 311 FT LEFT OF CENTERLINE, 112 FT AGL/1031 FT MSL. POLE 3193 FT FROM DER, 308 FT LEFT OF CENTERLINE, 112 AGL/1030 MSL.

PHOENIX-MESA GATEWAY:

NOTE: RWY 30L/C/R, TREES BEGINNING 351 FT FROM DER, 351 FT LEFT OF CENTERLINE, UP TO 20 FT AGL/1359 FT MSL. TREES BEGINNING 689 FT FROM DER, 398 FT RIGHT OF CENTERLINE, UP TO 20 FT AGL/1359 FT MSL.

PHOENIX SKY HARBOR INTL:

NOTE: RWY 7R, TRANSMISSION TOWERS AND POWER LINES, 3201 FT FROM DER, 1122 FT RIGHT OF CENTERLINE, UP TO 131 FT AGL/1260 FT MSL. NOTE: RWY 8, MULTIPLE LT POLES, BEGINNING 2539 FT FROM DER, 900 FT LEFT OF CENTERLINE, UP TO 82 FT AGL/1234 FT MSL. LT POLE, 1639 FT FROM DER, 793 FT RIGHT OF CENTERLINE, 46 FT AGL/1177 FT MSL. NOTE: RWY 25L, MULTIPLE LT POLES, BEGINNING 681 FT FROM DER, 521 FT LEFT OF CENTERLINE, UP TO 63 FT AGL/1166 FT MSL. SIGN, 902 FT FROM DER, 711 FT LEFT OF CENTERLINE, 64 FT AGL/1170 FT MSL. MULTIPLE LT POLES, BEGINNING 1519 FT FROM DER, 535 FT LEFT OF CENTERLINE, UP TO 99 FT AGL/1201 FT MSL. MULTIPLE LT POLES, BEGINNING 1919 FT FROM DER, 598 FT LEFT OF CENTERLINE, UP TO 90 FT AGL/1192 FT MSL. NOTE: RWY 26, POLE, 42 FT FROM DER, 440 FT LEFT OF CENTERLINE, 26 FT AGL/1135 FT MSL. FENCE, 176 FT FROM DER, 547 FT LEFT OF CENTERLINE, 11 FT AGL/1120 FT MSL. POLE, 315 FT FROM DER, 499 FT LEFT OF CENTERLINE, 11 FT AGL/1120 FT MSL. TREE, 763 FT FROM DER, 642 FT LEFT OF CENTERLINE, 24 FT AGL/1135 FT MSL. POLE, 1959 FT FROM DER, 923 FT LEFT OF CENTERLINE, 59 FT AGL/1163 FT MSL. POLE, 2312 FT FROM DER, 318 FT LEFT OF CENTERLINE, 66 FT AGL/1169 FT MSL. POLE, 2336 FT FROM DER, 578 FT LEFT OF CENTERLINE, 67 FT AGL/1170 FT MSL. POLE, 78 FT FROM DER, 456 FT RIGHT OF CENTERLINE, 32 FT AGL/1142 FT MSL. POLE, 82 FT FROM DER, 64 FT RIGHT OF CENTERLINE, 18 FT AGL/1127 FT MSL. TREE, 118 FT FROM DER, 294 FT RIGHT OF CENTERLINE, 22 FT AGL/1133 FT MSL. TREE, 239 FT FROM DER, 214 FT RIGHT OF CENTERLINE, 22 FT AGL/1133 FT MSL. TREE, 414 FT FROM DER, 522 FT RIGHT OF CENTERLINE, 24 FT AGL/1135 FT MSL. SIGN, 520 FT FROM DER, 567 FT RIGHT OF CENTERLINE, 16 FT AGL/1125 FT MSL. POLE, 2301 FT FROM DER, 193 FT RIGHT OF CENTERLINE, 69 FT AGL/1171 FT MSL. POLE, 2302 FT FROM DER, 661 FT RIGHT OF CENTERLINE, 68 FT AGL/1171 FT MSL.

SCOTTSDALE:

NOTE: RWY 3, MULTIPLE LIGHT STANDARDS BEGINNING 63 FT FROM DER, 445 FT LEFT OF CENTERLINE, UP TO 44 FT AGL/1554 FT MSL. HOIST ON DIKE 878 FT FROM DER, 735 FT LEFT OF CENTERLINE, 51 FT AGL/1561 FT MSL. DIKE BEGINNING 1066 FT FROM DER, 316 FT LEFT OF CENTERLINE, 38 FT AGL/1548 FT MSL. DAY MARKER ON DIKE 1230 FT FROM DER, 5 FT LEFT OF CENTERLINE, 39 FT AGL/1549 FT MSL. TREE 765 FT FROM DER, 115 FT LEFT OF CENTERLINE, 22 FT AGL/1532 FT MSL. ROAD BEGINNING 647 FT FROM DER, 296 FT LEFT OF CENTERLINE, 19 FT AGL/1529 FT MSL. FENCE BEGINNING 5 FT FROM DER, 338 FT RIGHT OF CENTERLINE, 6 FT AGL/1511 FT MSL. LIGHT STANDARD 1013 FT FROM DER, 430 FT RIGHT OF CENTERLINE, 44 FT AGL/1552 FT MSL.

NOTE: RWY 21, TREES 1072 FT FROM DER, 426 FT RIGHT OF CENTERLINE, 53 FT AGL/1497 FT MSL. BUILDING 316 FT FROM DER, 537 FT RIGHT OF CENTERLINE, 23 FT AGL/1467 FT MSL. TREE 2087 FT FROM DER, 418 FT LEFT OF CENTERLINE, 61 FT AGL/1505 FT MSL. TREE 1432 FT FROM DER, 438 FT RIGHT OF CENTERLINE, 38 FT AGL/1482 FT MSL. TREE 2234 FT FROM DER, 559 FT LEFT OF CENTERLINE, 58 FT AGL/1502 FT MSL.

QUALITY
3
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

CONTROLLING OBSTACLES:

SCOTTSDALE:

RWY 3: 3039 FT MSL AAO 334147.51 N/1115119.13W (CG) AND 3639 FT MSL AAO 334854.37N/1115628.61W (CTA)

PHOENIX DEER VALLEY:

RWY 25L/R: 2479 FT MSL AAO 334504.94N/1120513.74W (CG) AND 4159 FT MSL AAO 334109.72N/1114920.69W (CTA)

PHOENIX SKY HARBOR INTL:

RWY 26: 1599 FT MSL BUILDING 332650.76N/1120424.48W

LOST COMMUNICATIONS PROCEDURES:**ADDITIONAL FLIGHT DATA:**

REFERENCE MAG VAR: KPHX 12E EPOCH YR: 2000 DME/DME/IRU

ASSESSMENT: SAT (RNP 2.0)

ALL AIRPORTS - CHART: TOP ALTITUDE: 8000

PILOT NAVIGATION AREA:

10NM ARC CENTERED ON QUAKY (IF), CW

FROM: POINT A (BEARING 297.77 TO QUAKY)

TO: POINT B (BEARING 027.77 TO QUAKY)

MINIMUM ALTITUDE: 10500

CHART: MEA/MOCA FROM QUAKY TO SNOBL 14600/8100

AIRPORTS SERVED:

PHOENIX SKY HARBOR INTL, PHOENIX, AZ

PHOENIX-MESA GATEWAY, MESA, AZ

CHANDLER MUNI, CHANDLER, AZ

PHOENIX GOODYEAR, GOODYEAR, AZ

SCOTTSDALE, SCOTTSDALE, AZ

PHOENIX DEER VALLEY, PHOENIX, AZ

GLENDALE MUNI, GLENDALE, AZ

COMMUNICATIONS:

CHANDLER MUNI: ATIS, GND CON, CHD ATCT, PHOENIX DEP CON

PHOENIX DEER VALLEY: ATIS, CLNC DEL, GND CON, DVT ATCT, PHOENIX DEP CON

GLENDALE MUNI: ATIS, GND CON, GEU ATCT, PHOENIX DEP CON, LUKE DEP CON

PHOENIX GOODYEAR: ATIS, GND CON, GYR ATCT, PHOENIX DEP CON, LUKE DEP CON



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

PHOENIX-MESA GATEWAY: ATIS, CLNC DEL, GND CON, IWA ATCT, PHOENIX DEP CON

PHOENIX SKY HARBOR INTL: ATIS, CLNC DEL, GND CON, PHX ATCT, PHOENIX DEP CON

SCOTTSDALE: ATIS, CLNC DEL, GND CON, SDL ATCT, PHOENIX DEP CON

FIXES AND/OR NAVAIDS:



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
SNOBL	FOUR	SNOBL4.SNOBL	THREE	6/25/2015	21 JUL 2016

REMARKS:

KPHX CLIMB GRADIENTS AND CLIMB TO ALTITUDES DETERMINED BY DME/DME COVERAGE FOR NON-GPS EQUIPPED AIRCRAFT.

KDVT RWY 25L/R AND KSDL RWY 21 CLIMB GRADIENTS AND CLIMB TO ALTITUDE DETERMINED BY LOCATION OF 4600 MVA AND PROXIMITY TO HIGHER MVAS. KSDL: ATC WILL ASSIGN HEADING 335 OR AS ASSIGNED IN ACCORDANCE WITH DVA DATED 6/23/2014.

KDVT: ATC WILL ASSIGN HEADING 320 OR AS ASSIGNED IN ACCORDANCE WITH DVA DATED 6/30/2014.

SATELLITE AIRPORTS WERE MADE GPS REQUIRED DUE TO A HIGH PNA GRID ANALYSIS ALTITUDE ON SOME OF THE PNA SIDS. ELIMINATING THE PNA DME/DME/IRU GRID ANALYSIS REDUCED THE PNA ALTITUDE TO A MANAGABLE VECTORING ALTITUDE. KPHX RETAINED DME/DME/IRU OPERATIONS DUE TO HAVING A DEFINED ROUTE TO THE IDF AND DUE TO APPROXIMATELY 20 PERCENT OF THE DEPARTURES UTILIZING DME/DME/IRU NAVIGATION.

KGEU RWY 19 AND KGYR RWY 21 UTILIZE A HEADING FOR DEPARTURES WITHIN THE DVA RANGE FOR EACH RUNWAY WHICH IS CLOSEST TO THE RUNWAY ALIGNMENT SINCE THE RUNWAY ALIGNMENT IS NOT WITHIN THE USABLE DVA RANGE FOR VECTORING AIRCRAFT.

COORDINATED WITH:

Apr 13, 2016

ALPA, AOPA, ATA, NBAA, ZAB, PHOENIX APP CON, KPHX ATCT, WFPT.

CHANGES:

1. PHOENIX GOODYEAR (KGYR) RWY 3/21 INITIAL CLIMB HEADINGS CHANGED FROM 026 AND 225 TO 028 AND 228.
2. PHOENIX GOODYEAR (KGYR) TAKEOFF OBSTACLE NOTES UPDATED.
3. PHOENIX-MESA GATEWAY PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS RWY 12L/C/R CHANGED FROM STANDARD TO STANDARD WITH A MINIMUM CLIMB OF 250 FT/NM TO 3100.
4. CHANDLER (KCHD) TAKEOFF OBSTACLE NOTES UPDATED.

REASON:

1. AIRPORT (KGYR) MAGNETIC VARIATION ROTATION FROM E13 TO E10.
2. RWY CONSTRUCTION MOVED RWY 300 FT SOUTH.
3. TO MATCH PUBLISHED DVA MINIMUMS.
4. TO MATCH CURRENT PUBLISHED NOTES.



DEPARTURE (DATA RECORD)

DP Name		Number		DP Computer Code		Superseded Number		Dated	Effective Date
SNOWL RNAV		FOUR		SNOWL4.SNOWL		THREE		6/25/2015	21 JUL 2016
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW07L (AER)	332551.81N/1120137.56W	N	-	-	-	-			
1640 MSL	-	-	-	VA	090.04	-			CG 500 FT/NM TO 1640
SPRKY	332609.01N/1115327.82W	Y	FO	DF	-	-			
GOALY	333905.62N/1115011.78W	Y	FB	DF	-	013.20	AT/BELOW 9000		LEFT TURN
QUAKY	340527.51N/1115608.08W	Y	FB	TF	349.39	026.78			CG 230 FT/NM TO 10000
RW07R (AER)	332543.89N/1120137.57W	N	-	-	-	-			
1640 MSL	-	-	-	VA	090.03	-			CG 500 FT/NM TO 1640
SPRKY	332609.01N/1115327.82W	Y	FO	DF	-	-			
GOALY	333905.62N/1115011.78W	Y	FB	DF	-	013.20	AT/BELOW 9000		LEFT TURN
QUAKY	340527.51N/1115608.08W	Y	FB	TF	349.39	026.78			CG 230 FT/NM TO 10000
RW08 (AER)*	332627.09N/1120136.66W*	N	-	-	-	-			*DISPL THLD (898.0 FT)
1640 MSL	-	-	-	VA	090.06	-			CG 500 FT/NM TO 1640
SPRKY	332609.01N/1115327.82W	Y	FO	DF	-	-			
GOALY	333905.62N/1115011.78W	Y	FB	DF	-	013.20	AT/BELOW 9000		LEFT TURN
QUAKY	340527.51N/1115608.08W	Y	FB	TF	349.39	026.78			CG 300 FT/NM TO 10000
RW25L (AER)	332543.84N/1120005.54W	N	-	-	-	-			
	332543.96N/1120415.46W	-	-	VI	270.05	3.49			CG 500 FT/NM TO 2140
TWSND	333144.74N/1121022.80W	Y	FB	CF	319.50	7.89			RECOMMENDED NAVAID PXR VORTAC
OXYGN	333656.05N/1121015.16W	Y	FB	TF	001.18	5.18			
ZILUB	334458.32N/1120001.23W	Y	FB	TF	046.74	11.72			
QUAKY	340527.51N/1115608.08W	Y	FB	TF	008.97	20.70			
RW25R (AER)	332551.73N/1115936.05W	N	-	-	-	-			
	332551.89N/1120423.52W	-	-	VI	270.06	4.01			CG 500 FT/NM TO 2140
TWSND	333144.74N/1121022.80W	Y	FB	CF	319.50	7.72			RECOMMENDED NAVAID PXR VORTAC
OXYGN	333656.05N/1121015.16W	Y	FB	TF	001.18	5.18			
ZILUB	334458.32N/1120001.23W	Y	FB	TF	046.74	11.72			
QUAKY	340527.51N/1115608.08W	Y	FB	TF	008.97	20.70			

QUALITY
3

QUALITY
3
CHECKED

DEPARTURE (DATA RECORD)

DP Name		Number		DP Computer Code		Superseded Number		Dated	Effective Date
SNOB L RNAV		FOUR		SNOB L4.SNOB L		THREE		6/25/2015	21 JUL 2016
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW26 (AER)	332626.96N/1115931.69W	N	-	-	-	-			
	332627.29N/1120459.51W	-	-	VI	270.08	4.57			CG 500 FT/NM TO 2140
TWSND	333144.74N/1121022.80W	Y	FB	CF	319.50	6.94			RECOMMENDED NAVAID PXR VORTAC
OXYGN	333656.05N/1121015.16W	Y	FB	TF	001.18	5.18			
ZILUB	334458.32N/1120001.23W	Y	FB	TF	046.74	11.72			
QUAKY	340527.51N/1115608.08W	Y	FB	TF	008.97	20.70			
QUAKY	340527.51N/1115608.08W	Y	-	IF	-	-			
SNOB L	342550.94N/1115823.17W	Y	FB	TF	354.77	20.44			
SNOB L	342550.94N/1115823.17W	Y	-	IF	-	-			SNOB L4.CARTL
CARTL	344552.98N/1120036.29W	Y	FB	TF	354.78	20.08			
SNOB L	342550.94N/1115823.17W	Y	-	IF	-	-			SNOB L4.GCN
CARTL	344552.98N/1120036.29W	Y	FB	TF	354.78	20.08			
LOFTS	352143.99N/1120439.65W	Y	FB	TF	354.70	35.95			
RIMMM	353154.24N/1120540.39W	Y	FB	TF	355.35	10.19			
GCN	355737.22N/1120845.77W	Y	FB	TF	354.42	25.80			
SNOB L	342550.94N/1115823.17W	Y	-	IF	-	-			SNOB L4.JARPA
CARTL	344552.98N/1120036.29W	Y	FB	TF	354.78	20.08			
JARPA	354222.46N/1094719.99W	Y	FB	TF	062.04	122.88			
SNOB L	342550.94N/1115823.17W	Y	-	IF	-	-			SNOB L4.RIMMM
CARTL	344552.98N/1120036.29W	Y	FB	TF	354.78	20.08			
LOFTS	352143.99N/1120439.65W	Y	FB	TF	354.70	35.95			
RIMMM	353154.24N/1120540.39W	Y	FB	TF	355.35	10.19			
SNOB L	342550.94N/1115823.17W	Y	-	IF	-	-			SNOB L4.YOOPR
CARTL	344552.98N/1120036.29W	Y	FB	TF	354.78	20.08			
YOOPR	353924.72N/1102606.72W	Y	FB	TF	054.93	94.08			

QUALITY
3
CHECKED