

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
ST. JOHNS	NINE	SJN9.SJN	EIGHT	06/25/2015	28 FEB 2019

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☐

DP ROUTE DESCRIPTION:

TAKEOFF RWY 7L: CLIMB HEADING 078.04 TO 1550, THEN CLIMBING LEFT TURN HEADING 075.00. AT 4.00 DME EAST OF PXR VORTAC, CLIMBING LEFT TURN HEADING 045.00 TO PXR R-054 TO SJN VORTAC, MAINTAIN 8000. THENCE...

TAKEOFF RWY 7R: CLIMB HEADING 078.03 TO 1550, THEN CLIMBING LEFT TURN HEADING 070.00. AT 4.00 DME EAST OF PXR VORTAC, CLIMBING LEFT TURN HEADING 045.00 TO PXR R-054 TO SJN VORTAC, MAINTAIN 8000. THENCE...

TAKEOFF RWY 8: CLIMB HEADING 078.06 TO 1550, THEN CLIMBING RIGHT TURN HEADING 080.00. AT 4.00 DME EAST OF PXR VORTAC, CLIMBING LEFT TURN HEADING 045.00 TO PXR R-054 TO SJN VORTAC, MAINTAIN 8000. THENCE...

TAKEOFF RWY 25L: CLIMB HEADING 258.04 TO 1550, THEN CLIMBING RIGHT TURN HEADING 265.00. AT 9.00 DME WEST OF PXR VORTAC, CLIMBING RIGHT TURN HEADING 360.00, MAINTAIN 8000 FOR RADAR VECTORS TO PXR R-054 TO SJN VORTAC. THENCE...

TAKEOFF RWY 25R: CLIMB HEADING 258.05 TO 1550, THEN CLIMBING RIGHT TURN HEADING 260.00. AT 9.00 DME WEST OF PXR VORTAC, CLIMBING RIGHT TURN HEADING 360.00, MAINTAIN 8000 FOR RADAR VECTORS TO PXR R-054 TO SJN VORTAC. THENCE...

TAKEOFF RWY 26: CLIMB HEADING 258.08 TO 1550, THEN CLIMBING RIGHT TURN HEADING 260.00. AT 9.00 DME WEST OF PXR VORTAC, CLIMBING RIGHT TURN HEADING 360.00, MAINTAIN 8000 FOR RADAR VECTORS TO PXR R-054 TO SJN VORTAC. THENCE...

... (TRANSITION). EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
ALBUQUERQUE	SJN9.ABQ	SJN VORTAC	ABQ VORTAC	059.46 (SJN R-059, ABQ R-240)	120.92	12000	11100	

PROCEDURAL DATA NOTES:

NOTE: RESTRICTED TO TURBOJET AND TURBOPROP AIRCRAFT ONLY.

NOTE: RADAR AND DME REQUIRED.

NOTE: AIRCRAFT FILING OVER ACH, LBL, ONM, CNX, PNH, MMB, TCC, IRW AND TXO FILE BALDY DEPARTURE.

NOTE: AIRCRAFT FILING OVER CIM, FTI AND GCK FILE ST. JOHNS DEPARTURE.

TAKEOFF MINIMUMS:

RWY 7L, 7R, 8: STANDARD WITH MINIMUM CLIMB OF 350FT PER NM TO 8000.

RWY 25L, 25R, 26: STANDARD WITH MINIMUM CLIMB OF 350FT PER NM TO 8000.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
ST. JOHNS	NINE	SJN9.SJN	EIGHT	06/25/2015	28 FEB 2019

LOST COMMUNICATIONS PROCEDURES:

EXPECT FILED ALTITUDE 3 MINUTES AFTER DEPARTURE.

ADDITIONAL FLIGHT DATA:

CHART COP: PXR 67/SJN 86.

CHART: V190, J18.

CHART: TOP ALTITUDE: 8000

REFERENCE MAG VAR: KPHX 12E EPOCH YR: 2000.

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
PHOENIX SKY HARBOR INTL	PHOENIX	AZ

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON (NORTH)(SOUTH), PHOENIX TOWER, PHOENIX DEP CON.

FIXES AND/OR NAVAIDS:

FORPE

REMARKS:

ABBREVIATED AMENDMENT

FLIGHT INSPECTED BY:

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT: FLIGHT INSPECTION REVIEW NOT REQUIRED.

OFFICE SYMBOL:

DATE:
Digitally signed by

DAVID DANNER

Jan 17, 2019

DEVELOPED BY:

RUSS ROSLEWSKI

Digitally signed by

RUSSELL ROSLEWSKI

Oct 19, 2018

OFFICE SYMBOL:

AJV-5421

DATE:

10/01/2018

APPROVED BY:

JULIE MORGAN

Digitally signed by

DAVID DANNER

Jan 17, 2019

OFFICE SYMBOL:

AJV-5420

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A	ALPA	AOPA	APA	HAI	NBAA
☒	☒	☒	☒	☐	☒

OTHER:

ZAB, PHX TRACON, APT MGR, AZ ST AERO DIR.

CHANGES - REASONS:

1. REMOVED NOTE REGARDING MAXXO DEPARTURE - MAXXO DEPARTURE HAS BEEN CANCELED.
2. REMOVED TAKEOFF OBSTACLE NOTES AND REPLACED WITH NOTE TO SEE 8260-15A - AFS MEMO DATED 12/21/2017.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
ST. JOHNS	NINE	SJN9.SJN	EIGHT	06/25/2015	28 FEB 2019

3. DP ROUTE DESCRIPTION, TAKEOFF RWY 25L, 25R, 26, CHANGED "EXPECT RADAR VECTORS" TO "FOR RADAR VECTORS" - 8260.46F REMOVED "EXPECT" FROM RADAR VECTOR WORDING.
4. DP ROUTE DESCRIPTION, CHANGED "... VIA TRANSITION" TO "... (TRANSITION)" - 8260.46F WORDING.
5. PROCEDURAL DATA NOTES, DELETED NOTE REFERENCING SILOW DEPARTURE - SILOW DEPARTURE CANCELED.
6. PROCEDURAL DATA NOTES, ADDED NOTE REFERENCING BALDY DEPARTURE - ATC REQUEST.
7. ADDITIONAL FLIGHT DATA, ADDED REFERENCE MAG VAR - 8260.46F REQUIREMENT.

1/17/19: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 10/29/18:
TXX CHANGED TO TCC IN PROCEDURAL DATA NOTES.

