

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LP: RW28 LNAV: RW28 CLIMB TO 2800 DIRECT BRUNR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 094.22 INBOUND. CHART FAS OBST: 1040 TOWER 441906N/0885502W FAS OBST: 1009 AAO 441915N/0885518W CHART VDP AT 1.36 NM TO RW28. WAAS CHANNEL # 42621 REFERENCE PATH ID: W28A CHART CIRCLING ICON. FNDRY TO RW28: 3.00/40. LTP HAE: 209 M						
BIPID		WWEGA (TF) (FO) (RNP 2.00)			159.77 / 14.88			2800								
BECKY (IAF)		WWEGA (NOPT) (TF) (FB) (RNP 1.00)			203.61 / 15.15			2800								
OSH VORTAC (IAF)		WWEGA (NOPT) (TF) (FB) (RNP 1.00)			339.98 / 21.19			2800								
WWEGA (IF/IAF)		FNDRY (TF) (FB) (RNP 1.00)			274.66 / 6.29			2700								
FNDRY (FAF)		RW28 (MAP) (TF) (FO) (RNP 0.30)			274.55 / 5.82											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E WWEGA, RT, 274.66 INBOUND, 2800 FT. IN LIEU OF PT (IAF) 3. FAC: 274.55 FAF: FNDRY DIST FAF TO MAP: 5.82 THLD: 5.82 4. MIN. ALT: WWEGA 2800, FNDRY 2700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW28 2800																
											MAG VAR: 1W			EPOCH YEAR: 1995		
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT											ALTERNATE: N A		STANDARD			
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LP MDA	1260	1	433	1260	1	433	1260	1 3/8	433	1260	1 3/8	433				
LNAV MDA	1340	1	513	1340	1	513	1340	1 3/8	513	1340	1 3/8	513				
CIRCLING	1380	1	540	1420	1	580	1420	1 1/2	580	1500	2	660				
NOTES: CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON OSH VORTAC AIRWAY RADIALS 307 CW 023.																
CITY AND STATE		ELEVATION: 840 TDZE: 827			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:				
WAUPACA, WI		AIRPORT NAME: WAUPACA MUNI					RNAV (GPS) RWY 28, AMDT 2					AMDT: 1A				
							27 APRIL 2017					DATED 04/02/2015				

 QUALITY
10
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW28 (MAP)	1240 MSL	274.55	
1240 MSL	BRUNR (DF) (FO) (RNP 1.00)		2800

CITY AND STATE
WAUPACA, WI

ELEVATION: 840 TDZE: 827
AIRPORT NAME:
WAUPACA MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 28, AMDT 2
27 APRIL 2017

SUP: 10
AMDT: 1A
DATED: 04/02/2015

QUALITY
10
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPCZ
RUNWAY	RW28
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W28A
LTP/FTP LATITUDE	441957.0300N
LTP/FTP LONGITUDE	0890047.0055W
LTP/FTP ELLIPSOIDAL HEIGHT	+02090
FPAP LATITUDE	442002.3765N
FPAP LONGITUDE	0890250.9200W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1168
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

<u>CRC REMAINDER</u>	9DAAB12F
----------------------	----------

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02454
FPAP ORTHOMETRIC HEIGHT	+02454

CITY AND STATE

WAUPACA, WI

ELEVATION: 840

TDZE: 827

AIRPORT NAME:

WAUPACA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 28, AMDT 2

27 APRIL 2017

SUP:

AMDT:

DATED:

 QUALITY
10
CHECKED

1A

04/02/2015