

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ACK VOR/DME	ASKEW INT/MVY 16.00 DME/RADAR	335.18 / 24.27	2000
MVY VOR/DME (IAF)	PAULI INT/6.00 DME (NOPT)	058.00 / 6.00	2000
PAULI INT/6.00 DME (IF)	ASKEW INT/MVY 16.00 DME/RADAR	058.00 / 10.00 (MVY R-058)	2000

MAP: 5.98 NM AFTER ASKEW INT/MVY 16.00 DME/RADAR OR AT MVY 21.98 DME FIX

CLIMB TO 2000 DIRECT LFV VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.

ALTERNATE MA (DO NOT CHART): CLIMBING RIGHT TURN TO 1700 ON HEADING 075 AND MVY R-059 TO BOGEY INT/MVY 26.89 DME AND HOLD NE, RT, 238.92 INBOUND.

ADDITIONAL FLIGHT DATA:
 HOLD S, LT, 360.00 INBOUND.
 CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD NE BOGEY INT/MVY 26.89 DME, RT, 238.92 INBOUND.
 FAS OBST: 279 AAO 413829N/0702208W
 CHART IN PLANVIEW: BOGEY INT/MVY 26.89 DME.
 CHART CIRCLING ICON.
 ASKEW TO RW06: 3.02/37
 FAC IS A FLIGHT CHECK VALUE

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW ASKEW, RT, 058.00 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
- FAC 058.00 FAF ASKEW INT/MVY 16.00 DME/RADAR DIST FAF TO MAP 5.98 THLD 5.98
- MIN. ALT ASKEW 2000
- MSA FROM: MVY VOR/DME 360-270 1700, 270-360 2100

MAG VAR: 15W EPOCH YEAR: 1980

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	@			
CATEGORY =====>	A	B	C	D	E
	MDA VIS HAT/HAA	MDA VIS HAT/HAA	MDA VIS HAT/HAA	MDA VIS HAT/HAA	MDA VIS HAT/HAA
S-06	900 1 855	900 1 1/4 855	900 2 1/2 855	900 2 1/2 855	
CIRCLING	900 1 1/4 846	900 1 1/4 846	900 2 1/2 846	900 2 3/4 846	

NOTES:
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING AND INCREASE ALL MDA'S 40 FEET AND INCREASE CIRCLING CAT C/D VISIBILITY 1/4 MILE.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 @ CAT A, B 900-2, CAT C 900-2 1/2, CAT D 900-2 3/4



CITY AND STATE HYANNIS, MA	ELEVATION: 54 TDZE: 45	FACILITY IDENTIFIER: MVY	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
	AIRPORT NAME: BARNSTABLE MUNI-BOARDMAN/POLANDO FIELD		VOR RWY 6, AMDT 10	AMDT 9A
			10 NOVEMBER 2016	DATE 09/25/2008