U.S. Department of Transportation

800 Independence Ave., S.W. Washington, D.C. 20591

Federal Aviation Administration

Transmittal Letter 15-17

July 2, 2015

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
20-Aug-15	NE	Cozad	Cozad Muni	5/7288	06/29/15	Takeoff Minimums and (Obstacle) DP, Amdt 1

EFFECTIVE 20 AUGUST 2015

FDC **5/7288** CZD ODP COZAD MUNI, COZAD, NE. TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES AMDT 1... TAKE-OFF MINIMUMS: RWY 13, 200-1 OR STANDARD WITH MINIMUM CLIMB OF 372 FEET PER NM TO 2800. CHANGE NOTED OBSTACLE FOR RWY 13: ANTENNA ON GRAIN ELEVATOR, 3672' FROM DER, 392' LEFT OF CENTERLINE, 189' AGL/2678' MSL. TO READ: ELEVATOR 3671 FEET FROM DER, 392 FEET LEFT OF CENTERLINE, 192 FEET AGL/2668 FEET MSL. ALL OTHER DATA REMAINS AS PUBLISHED. THIS IS TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES, AMDT 1A. 1506291119-PERM