

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
NPLII	TWO	NPLII2.SAKKI	ONE	09 FEB 2012	20 AUG 2015

TYPE: SID RNAV

DP ROUTE DESCRIPTION:

TAKEOFF RUNWAY 2: CLIMB TO ASSIGNED ALTITUDE ON HEADING 023.97 TO INTERCEPT COURSE 320.02 TO CROSS WMAUI AT OR ABOVE 3200, AND ON TRACK 275.94 TO CROSS ROXZZ AT OR ABOVE 4000, AND ON TRACK 251.10 TO CROSS ISSNO AT OR ABOVE 7000, AND ON TRACK 248.95 TO CROSS AARES AT OR ABOVE 14000, AND ON TRACK 248.81 TO SAKKI.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes
-----------------	---------------------------	--------------------	---------------	--------	----------	-----	------	--------------------------

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

TAKEOFF MINIMUMS RWY 5, 20, 23, NA-AIR TRAFFIC.
RWY 2 STANDARD WITH MINIMUM CLIMB OF 355 FEET PER NM TO 11200.
NOTE: RNAV 1.
NOTE: GPS REQUIRED.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 2 BUSH/TREES BEGINNING 190 FT FROM DER, 362 FT LEFT OF CENTERLINE, UP TO 60 FT AGL/79 FT MSL. PIPE ON BUILDING 339 FT FROM DER, 289 FT RIGHT OF CENTERLINE, 20 FT AGL/25 FT MSL. BUSHES BEGINNING 902 FT FROM DER, 637 FT RIGHT OF CENTERLINE, UP TO 20 FT AGL/39 FT MSL.

CONTROLLING OBSTACLES:

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: PHOG 11E EPOCH YR:90
CHART: TOP ALTITUDE: ASSIGNED BY ATC

AIRPORTS SERVED:

KAHULUI

KAHULUI , HI



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
NPLII	TWO	NPLII2.SAKKI	ONE	09 FEB 2012	20 AUG 2015

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, MAUI TWR, CTAF, HCF APP CON

FIXES AND/OR NAVAIDS:

REMARKS:

355 TO 11200 CLIMB GRADIENT DRIVEN BY BOTH ATC DIRECTED VI LEG TURN LOCATION AND MANDATORY CROSSING ALTITUDE RESTRICTION AT ARRES.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
NPLII	TWO	NPLII2.SAKKI	ONE	09 FEB 2012	20 AUG 2015

CHANGES:

ADDED: CHART TOP ALTITUDE: ASSIGNED BY ATC

REASONS:

ATC REQUEST



DEPARTURE (DATA RECORD)

DP Name		Number		DP Computer Code		Superseded Number		Dated	Effective Date
NPLII		TWO		NPLII2.SAKKI		ONE		09 FEB 2012	20 AUG 2015
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW02 (AER)	205320.90N/1562610.75W	N	-	-	-	-			CG 355 FT /NM TO 11200
	205534.19N/1562431.53W	-	-	VI	034.97	2.70			
WMAUI	210400.00N/1562930.00W	Y	FB	CF	331.02	9.60	AT/ABOVE 3200		
ROXZZ	210500.00N/1563300.00W	Y	FB	TF	286.94	3.42	AT/ABOVE 4000		
ISSNO	210336.00N/1564342.00W	Y	FB	TF	262.10	10.10	AT/ABOVE 7000		
AARES	205955.00N/1570542.00W	Y	FB	TF	259.95	20.91	AT/ABOVE 14000		
SAKKI	205554.31N/1572918.03W	Y	FB	TF	259.81	22.45			