

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR OR TACAN STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
R-075 SGF VORTAC CCW (IAF)	R-016 SGF VORTAC	7.00 DME ARC	3400
R-272 SGF VORTAC CW (IAF)	R-016 SGF VORTAC	7.00 DME ARC	3400
R-016/7.00 DME	SGF VORTAC	195.84/7.00	3400

MAP: 6.53 MILES AFTER SGF VORTAC OR AT SGF 6.53 DME

CLIMB TO 3000 THEN RIGHT TURN TO INTERCEPT SGF R-206 TO BILIE INT/SGF 21.79 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD SW, RT, 026 INBOUND

FAS OBST: 1419 TREE 371515/932136

SGF VORTAC TO RWY 20: 3.01/49

CHART VDP AT 5.30 DME

DISTANCE VDP TO THLD 1.23 MILES

1. PT L SIDE OF COURSE 015.84 OUTBOUND 3400 FT WITHIN 15 MILES OF SGF VORTAC (IAF)

2. _____

3. FAC 195.84 FAF SGF VORTAC DIST FAF TO MAP 6.53 THLD 6.53

4. MIN. ALT SGF VORTAC 3400

8. MSA FROM: SGF VORTAC 220-070 2800, 070-220 4600

MAG VAR: 4E

EPOCH YEAR: 90

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: N A			STANDARD			
			A			B			C			D			E
CATEGORY	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-20	1700	3/4	439	1700	3/4	439	1700	1 1/4	439	1700	1 1/2	439	1700	1 1/2	439
CIRCLING	1740	1	473	1740	1	473	1740	1 1/2	473	1820	2	553	1860	2	593

NOTES:

CITY AND STATE	ELEVATION: 1267 TDZE: 1261	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP
SPRINGFIELD, MO	AIRPORT NAME: SPRINGFIELD-BRANSON REGIONAL	SGF	30 DEC 99	AMDT 17
			VOR OR TACAN RWY 20, AMDT 18	DATED 12 NOV 92