

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW01							
AWNED (IAF)		BAQAV (NOPT) (FB)		274.34 / 8.00			1800		CLIMB TO 1700 DIRECT BIJUV AND HOLD.							
WIWHE (IAF)		BAQAV (NOPT) (FB)		094.17 / 8.25			1800									
BAQAV (IF/IAF)		AGMEQ (FB)		004.26 / 5.94			1800									
AGMEQ (FAF)		RW01 (MAP) (FO)		004.24 / 5.06												
RW01 (MAP)		412 MSL		004.24					ADDITIONAL FLIGHT DATA: HOLD N, RT, 184.26 INBOUND. CHART FAS OBST: 557 TWR 311151N/0822403W DISTANCE TO THLD FROM 272 HAT: 0.70 NM. CHART VDP AT 2.04 MILES TO RW01* *LNAV ONLY. WAAS CHANNEL # 56209 REFERENCE PATH ID: W01A CHART CIRCLING ICON LTP HAE: 12.6 M							
412 MSL		BIJUV (FO)					1700									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 5W EPOCH YEAR: 2005						
2. HOLD S BAQAV, RT, 004.26 INBOUND, 1800 FT. IN LIEU OF PT (IAF)																
3. FAC: 004.24 FAF: AGMEQ DIST FAF TO MAP: 5.06 THLD: 5.06																
4. MIN. ALT: BAQAV 1800, AGMEQ 1800																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: 1800 GS ALT AT: AGMEQ 1800 OM: _____ MM: _____ IM: _____																
7. GS ANGLE: 3.00 TCH: 55.0 34:1 IS NOT CLEAR																
8. MSA FROM: _____																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	423	7/8	283	423	7/8	283	423	7/8	283	423	7/8	283				
LNAV/VNAV DA	412	7/8	272	412	7/8	272	412	7/8	272	412	7/8	272				
LNAV MDA	820	1	680	820	1	680	820	1 7/8	680	820	1 7/8	680				
CIRCLING	820	1	679	820	1	679	860	2	719	860	2 1/4	719				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE ALMA ALTIMETER SETTING AND INCREASE LPV DA TO 473 FEET AND ALL VISIBILITIES 1/4 MILE, LNAV/VNAV DA TO 462 FEET AND ALL VISIBILITIES 1/8 MILE; INCREASE ALL MDA 60 FEET AND VISIBILITY CATS C AND D 1/8 MILE AND CIRCLING CATS C AND D VISIBILITIES 1/4 MILE. (SEE FORM 8260-10)																
CITY AND STATE WAYCROSS, GA		ELEVATION: 141 TDZE: 140 AIRPORT NAME: WAYCROSS-WARE COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 4 FEBRUARY 2016				SUP: RNAV (GPS) RWY 36 AMDT: 1 DATED 11/15/2012						

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F).

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: NIGHT LANDING RWY 5, 31 NA.

CHART NOTE: VDP AND BARO-VNAV NA WHEN USING ALMA ALTIMETER SETTING.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	274/30 CW 094/30 (NOPT)	BAQAV (IF/IAF) (FB)	1800
2.	184/30 CW 274/30	AWNED (IAF) (FB)	2100
3.	094/30 CW 184/30	WIWHE (IAF) (FB)	2300

QUALITY
23
CHECKED

CITY AND STATE

WAYCROSS, GA

ELEVATION: 141

TDZE: 140

AIRPORT NAME:

WAYCROSS-WARE COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, AMDT 2

4 FEBRUARY 2016

SUP: RNAV (GPS) RWY 36

AMDT: 1

DATED: 11/15/2012

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAYS
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	311420.1955N
LTP/FTP LONGITUDE	0822353.2670W
LTP/FTP ELLIPSOIDAL HEIGHT	+00126
FPAP LATITUDE	311549.4855N
FPAP LONGITUDE	0822354.6460W
THRESHOLD CROSSING HEIGHT (TCH)	00055.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0928
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

<u>CRC REMAINDER</u>	1A128683
----------------------	----------

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00408
FPAP ORTHOMETRIC HEIGHT	+00408

QUALITY
23
CHECKED

CITY AND STATE WAYCROSS, GA	ELEVATION: 141 TDZE: 140 AIRPORT NAME: WAYCROSS-WARE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 4 FEBRUARY 2016	SUP: RNAV (GPS) RWY 36
				AMDT: 1
				DATED: 11/15/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KAYS

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
AWNED	010	AWNED	IF	FB										E A
AWNED	020	BAQAV	TF	FB	1.0	274.3						AA 01800		EE B
BAQAV	010	BAQAV	HF	FO		004.3			R			AA 01800		EE A
WIWHE	010	WIWHE	IF	FB										E A
WIWHE	020	BAQAV	TF	FB	1.0	094.2						AA 01800		EE B
	010	BAQAV	IF	FB								AA 01800		E I
	020	AGMEQ	TF	FB	0.5	004.3						AA 01800		E F
	030	RW01	TF	FO	0.3	004.2		3.00				AT 00189		GY M
	040		CA	FB		004.2						AA 00412		M
	050	BIJUV	DF	FO								AA 01700		EY
	060	BIJUV	HM	FO		184.3			R			AA 01700		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
AGMEQ	N310916.00	W0822348.58
AWNED	N310324.71	W0821424.43
BAQAV	N310318.82	W0822343.20
BIJUV	N312602.37	W0822403.98
WIWHE	N310311.97	W0823319.57

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW01	N311420.20	W0822353.27	00134	55.0

QUALITY
23
CHECKED

CITY AND STATE WAYCROSS, GA	ELEVATION: 141 TDZE: 140	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 4 FEBRUARY 2016	SUP: RNAV (GPS) RWY 36
	AIRPORT NAME: WAYCROSS-WARE COUNTY			AMDT: 1
				DATED: 11/15/2012