

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**TACAN STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SKE TACAN	WEPUX/SKE 7.00 DME	050.00 / 7.00	3000
ILSCA/SKE 14.10 DME CW (IAF)	BLVIF/SKE 14.10 DME (NOPT)	14.10 DME ARC (SKE LR-041)	3000
SCAFB/SKE 14.10 DME CCW (IAF)	BLVIF/SKE 14.10 DME (NOPT)	14.10 DME ARC (SKE LR-059)	3000
BLVIF/SKE 14.10 DME (IF)	WEPUX/SKE 7.00 DME	230.00 / 7.10 (SKE R-050)	2000

**MAP: ZATUL/SKE 3.00 DME**  
  
**CLIMBING LEFT TURN TO 3000 ON HEADING 130 AND SKE TACAN R-107 TO DUTMY/SKE 14.11 DME AND HOLD.**

**ADDITIONAL FLIGHT DATA:**  
**HOLD E, RT, 287.09 INBOUND.**  
**CHART FAS OBST: 861 TOWER 383641N/0894530W**  
**CHART: ASR.**  
**CHART SKE R-010 AT ILSCA.**  
**CHART SKE R-090 AT SCAFB.**  
**CHART CIRCLING ICON.**  
**FAC CROSSES APPROACH END OF RWY 14L.**

- PT R SIDE OF COURSE 050.00 OUTBOUND 3000 FT WITHIN 15 MILES OF WEPUX (IAF)
- 
- FAC 230.00 FAF WEPUX/SKE 7.00 DME DIST FAF TO MAP \_\_\_\_\_ THLD \_\_\_\_\_
- MIN. ALT BLVIF 3000, WEPUX 2000
- MSA FROM: SKE TACAN 240-330 2700, 330-240 2200; ESA W/IN 100 NM 3500

MAG VAR: **2W** EPOCH YEAR: **2020**

**MINIMUMS**

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	@			
CATEGORY =====>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>
	MDA VIS HAT/HAA				
<b>CIRCLING</b>	<b>1180 2 1/4 721</b>	<b>1180 2 1/4 721</b>	<b>1240 2 1/4 781</b>	<b>1240 2 1/2 781</b>	<b>1240 2 3/4 781</b>

NOTES:  
**CHART PLANVIEW NOTE: RADAR REQUIRED.**  
**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ST. LOUIS DOWNTOWN ALTIMETER SETTING; INCREASE ALL MDA 60 FEET; INCREASE CIRCLING CAT C/D/E VISIBILITY 1/4 MILE.**

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.  
 @ CAT A, B, C 800-2 1/4, CAT D 800-2 1/2, CAT E 800-2 3/4



CITY AND STATE <b>BELLEVILLE, IL</b>	ELEVATION: <b>459</b> AIRPORT NAME: <b>SCOTT AFB/MIDAMERICA</b>	TDZE:	FACILITY IDENTIFIER: <b>SKE</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>TACAN-A, ORIG, 5/26/2016</b>	SUP <b>NONE</b>
					DATE