U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and attitudes are in feet, MSL. Attitudes are minimum attitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 24, STANDARD WITH MINIMUM CLIMB OF 310 FEET PER NM TO 1900, OR 1300 - 2 1/2 FOR CLIMB IN VISUAL CONDITIONS. RWY 6, NA, OBSTACLES.

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 24 - CLIMB HEADING 240.55 TO 1900 BEFORE PROCEEDING ON COURSE, OR FOR CLIMB IN VISUAL CONDITIONS CROSS GETTYSBURG RGNL AIRPORT AT OR ABOVE 1700 BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES: NOTE: RWY 24, VEHICLE ON ROAD 350' FROM DER, 61' LEFT OF CENTERLINE 17' AGL/576' MSL. TREES BEGINNING 273' FROM DER, 214' RIGHT OF CENTERLINE, UP TO 100' AGL/639' MSL.

(4) CONTROLLING OBSTACLES:

RWY 24: 1099 MSL AAO 394918.91N-0771936.45W, 2179 MSL AAO 395212.11N-0772447.91W. VCOA: 1083 MSL AAO 394924.32N-0771951.75W, 2179 MSL AAO 395212.11N-0772447.91W.



(8) Amdt. No.

ORIG

(5) City, State

GETTYSBURG, PA

(6) Airport

GETTYSBURG RGNL

(7) Effective Date

03 JUN 2010