

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA	
SSI VORTAC	JILAG (FB)	265.28 / 19.79	2000	CLIMB TO 2000 DIRECT IMOXE AND HOLD.	
AYS VORTAC	NANPE (FB)	125.81 / 31.36	2300		
JILAG (IAF)	HOPKO (NOPT) (FB)	282.33 / 5.68	2000		
NANPE (IAF)	HOPKO (NOPT) (FB)	102.22 / 5.00	2000	ADDITIONAL FLIGHT DATA: HOLD N, RT, 192.29 INBOUND. CHART 1091 TOWER 310824N/0815614W CHART 1087 TOWER 310923N/0815818W CHART BRUNSWICK AWOS-3 DISTANCE TO THLD FROM 331 HAT: 0.93 NM. WAAS CHANNEL # 90317 REFERENCE PATH ID: W01A CHART COASTAL 1 WEST MOA CHART COASTAL 4 MOA LTP HAE: -4.3 M	
HOPKO (IF/IAF)	FAYPU (FB)	012.27 / 6.34	2000		
FAYPU (FAF)	RW01 (MAP)	012.27 / 5.81			
RW01 (MAP)	416 MSL	012.27			
416 MSL	IMOXE (FO)		2000		

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S HOPKO, RT, 012.27 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
3. FAC: 012.27 FAF: DIST FAF TO MAP: THLD:
4. MIN. ALT: HOPKO 2000
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCP: 2000 GS ALT AT: FAYPU 2000 OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
8. MSA FROM: RW01 2700

MAG VAR: 6W EPOCH YEAR: 2010

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: NA	<input type="checkbox"/> X														
CATEGORY =====>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	416	1 1/4	331	416	1 1/4	331	416	1 1/4	331	416	1 1/4	331				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: USE BRUNSWICK GOLDEN ISLES ALTIMETER SETTING, WHEN NOT RECEIVED, USE WAYCROSS ALTIMETER SETTING AND INCREASE ALL DA 6 FEET AND ALL VISIBILITY 1/4 MILE.
 (SEE FORM 8260-10)



CITY AND STATE NAHUNTA, GA	ELEVATION: 85 TDZE: 85 AIRPORT NAME: BRANTLEY COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 1, ORIG 15 DEC 2011	SUP: AMDT: NONE DATED
-------------------------------	---	------------------------------	---	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON SSI VORTAC AIRWAY RADIALS 227 CW 302.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON AYS VORTAC AIRWAY RADIALS 136 CW 180.



CITY AND STATE NAHUNTA, GA	ELEVATION: 85 AIRPORT NAME: BRANTLEY COUNTY	TDZE: 85	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 1, ORIG 15 DEC 2011	SUP:
					AMDT: NONE
					DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	4J1
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Z
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	311202.1740N
LTP/FTP LONGITUDE	0815424.0695W
LTP/FTP ELLIPSOIDAL HEIGHT	-00043
FPAP LATITUDE	311330.9300N
FPAP LONGITUDE	0815412.7000W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 7062246D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00243
FPAP ORTHOMETRIC HEIGHT	+00243



CITY AND STATE NAHUNTA, GA	ELEVATION: 85 TDZE: 85 AIRPORT NAME: BRANTLEY COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 1, ORIG 15 DEC 2011	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

	1	2	3	4	5	6	7	8	9	0	1	2	3
NAVAID	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890
SUSAD	AYS	K7011020VTL	N31160993W082332320	N31160993W082332320E0000001551	NARWAYCROSS	I							
SUSAD	SSI	K7010980VTL	N31030184W081264545	N31030184W081264545W0040000101	NARBRUNSWICK	I							
WP	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890
SUSAEAENRT	FAYPU	K70 W	N31061483W081550849	W0059	NAR	FAYPU	I						
SUSAEAENRT	HOPKO	K70 W	N30595591W081555685	W0059	NAR	HOPKO	I						
SUSAEAENRT	IMOXE	K70 W	N31240890W081525084	W0060	NAR	IMOXE	I						
SUSAEAENRT	JILAG	K70 W	N30591842W081492260	W0059	NAR	JILAG	I						
SUSAEAENRT	NANPE	K70 W	N31002862W082014384	W0058	NAR	NANPE	I						
AIRPORT	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890
SUSAP	4J1 K7A4J1	0	040YHN31122190W081542160W006000085	1800018000C	MNAR	BRANTLEY COUNTY	I						
SEGMENT	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890
SUSAP	4J1 K7FR01-Z	AAYS	010AYS K7D 0V	IF		18000	A JS	I					
SUSAP	4J1 K7FR01-Z	AAYS	020NANPEK7EA0E	A 020TF	12580314	+ 02300	A JS	I					
SUSAP	4J1 K7FR01-Z	AAYS	030HOPKOK7EA0EE	B 010TF	10220050	+ 02000	A JS	I					
SUSAP	4J1 K7FR01-Z	AHOPKO	010HOPKOK7EA0EE	AR HF	01230040	+ 02000	18000	A JS	I				
SUSAP	4J1 K7FR01-Z	ASSI	010SSI K7D 0V	IF			18000	A JS	I				
SUSAP	4J1 K7FR01-Z	ASSI	020JILAGK7EA0E	A 020TF	26530198	+ 02000		A JS	I				
SUSAP	4J1 K7FR01-Z	ASSI	030HOPKOK7EA0EE	B 010TF	28230057	+ 02000		A JS	I				
SUSAP	4J1 K7FR01-Z	R	010HOPKOK7EA0E	I IF			18000	A JS	I				
SUSAP	4J1 K7FR01-Z	R	020FAYPUK7EA1E	F 051TF	01230063	+ 02000		RW01 K7PGA	JS I				
SUSAP	4J1 K7FR01-Z	R	020FAYPUK7EA2WALPV	N N					JS I				
SUSAP	4J1 K7FR01-Z	R	030RW01 K7PGOGY	M 031TF	01230058	00120	-300	A JS	I				
SUSAP	4J1 K7FR01-Z	R	040 0 M CA		0123	+ 00416		A JS	I				
SUSAP	4J1 K7FR01-Z	R	050IMOXEK7EA0EY	DF				A JS	I				
SUSAP	4J1 K7FR01-Z	R	060IMOXEK7EA0EE	R HM	19230040	+ 02000		A JS	I				



CITY AND STATE
NAHUNTA, GA

ELEVATION: 85 **TDZE: 85**
AIRPORT NAME:
 BRANTLEY COUNTY

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) Z RWY 1, ORIG
 15 DEC 2011

SUP:
AMDT: NONE
DATED:

