

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LP: RW03 LNAV: RW03											
EETEE		OVUVE (TF) (FB) (RNP 2.00)		283.86 / 7.70		3300		(DO NOT EXCEED 250 KIAS UNTIL KEWPI) CLIMB TO 1920 THEN CLIMBING LEFT TURN TO 3000 DIRECT KEWPI AND HOLD.											
OVUVE (IAF)		FAPOG (TF) (FB) (RNP 1.00)		311.84 / 8.19		3300													
GANTS (IAF)		FAPOG (TF) (FB) (RNP 1.00)		076.69 / 6.99		3300													
FAPOG (IF)		GABNE (TF) (FB) (RNP 1.00)		029.52 / 5.00		2500													
GABNE (FAF)		RW03 (MAP) (TF) (FO) (RNP 0.30)		029.52 / 4.79															
(SEE FORM 8260-10)								ADDITIONAL FLIGHT DATA: HOLD S, RT, 013.03 INBOUND. CHART FAS OBST: 1028 TREE 353725N/0795425W CHART FAS OBST: 1036 TREE 353703N/0795415W 1089 AAO 353433N/0795518W CHART VDP AT 1.50 NM TO RW03. WAAS CHANNEL # 86740 REFERENCE PATH ID: W03A CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES. LTP HAE: 174.1 M											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 8W EPOCH YEAR: 2000									
2. PROFILE STARTS AT FAPOG																			
3. FAC: 029.52 FAF: GABNE DIST FAF TO MAP: 4.79 THLD: 4.79																			
4. MIN. ALT: FAPOG 3300, GABNE 2500																			
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																			
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																			
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																			
8. MSA FROM: RW03 3700																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD @											
CATEGORY =====>		A		B		C		D		E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LP MDA	1280	1	609	1280	1	609	1280	1 3/4	609	1280	1 3/4	609							
LNAV MDA	1300	1	629	1300	1	629	1300	1 3/4	629	1300	1 3/4	629							
CIRCLING	1300	1	629	1360	1	689	1680	3	1009	1680	3	1009							
NOTES: CHART NOTE: RWY 3 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. @ CAT C, D 1100-3 CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EETEE ON V373 SOUTHBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GANTS ON V103 SOUTHBOUND AND V409 AND T202 SOUTHWEST BOUND.																			
CITY AND STATE ASHEBORO, NC		ELEVATION: 671 TDZE: 671 AIRPORT NAME: ASHEBORO RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 22 JUNE 2017						SUP: AMDT: ORIG-A DATED 09/18/2014							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW03 (MAP)	1920 MSL (CA)	029.52	1920
1920 MSL	KEWPI (DF) (FO) (RNP 1.00)		3000

QUALITY  
10  
CHECKED

CITY AND STATE  
ASHEBORO, NC

ELEVATION: 671 TDZE: 671  
AIRPORT NAME:  
ASHEBORO RGNL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 3, AMDT 1  
22 JUNE 2017

SUP:  
AMDT: ORIG-A  
DATED: 09/18/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KHBI
RUNWAY	RW03
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W03A
LTP/FTP LATITUDE	353850.9885N
LTP/FTP LONGITUDE	0795353.2900W
LTP/FTP ELLIPSOIDAL HEIGHT	+01741
FPAP LATITUDE	354013.9885N
FPAP LONGITUDE	0795313.1400W
THRESHOLD CROSSING HEIGHT (TCH)	00000.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	00.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 E5CCB96D

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+02044
FPAP ORTHOMETRIC HEIGHT	+02044

QUALITY  
10  
CHECKED

CITY AND STATE  ASHEBORO, NC	ELEVATION: 671 AIRPORT NAME:  ASHEBORO RGNL	TDZE: 671  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 3, AMDT 1 22 JUNE 2017	SUP:
				AMDT: ORIG-A
				DATED: 09/18/2014