

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
WIVEY	CIVIS (FB)	094.26 / 10.64	3000	LNAV: RW17
DSM VORTAC (IAF)	YOUTO (NOPT) (FB)	134.38 / 19.02	3000	CLIMB TO 1500 THEN CLIMBING LEFT TURN TO 3000 DIRECT YOUTO AND HOLD.
CIVIS (IAF)	YOUTO (NOPT) (FB)	086.97 / 5.99	3000	
YOUTO (IF/IAF)	OLLIS (FB)	177.06 / 6.04	2600	ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1146 TREE 410210N/0932157W OLLIS TO RW17: 3.00/40
OLLIS (FAF)	ZOBUP/1.90 NM TO RW17 (FB)	177.06 / 2.88		
ZOBUP/1.90 NM TO RW17 (SEE FORM 8260-10)	RW17 (MAP) (FO)	177.06 / 1.90		

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD N YOUTO, RT, 177.06 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 177.06 FAF: OLLIS DIST FAF TO MAP: 4.78 THLD: 4.78
- MIN. ALT: YOUTO 3000, OLLIS 2600, ZOBUP/1.90 NM TO RW17 1680
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW17 2800

MAG VAR: 3E EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1400	1	362	1400	1	362		NA			NA				
CIRCLING	1540	1	489	1540	1	489		NA			NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAMONI ALTIMETER SETTING AND INCREASE
 (SEE FORM 8260-10)



CITY AND STATE CHARITON, IA	ELEVATION: 1051 THRE: 1038 AIRPORT NAME: CHARITON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 1 05 APR 2012	SUP: AMDT: ORIG DATED 12/17/2009
--------------------------------	--	------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW17 (MAP)	1500 MSL	177.06	1500
1500 MSL	YOUTO (FO)		3000

NOTES, (CONT.):

ALL MDA 100 FEET.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON DSM VORTAC AIRWAY RADIALS 079 CW 141.
 CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 10 AND RWY 28 NA AT NIGHT.
 CHART NOTE: STRAIGHT-IN/CIRCLING RWY 17 PROCEDURE NA AT NIGHT.
 CHART NOTE: CIRCLING TO RWY 35 NA AT NIGHT.



CITY AND STATE CHARITON, IA	ELEVATION: 1051 THRE: 1038 AIRPORT NAME: CHARITON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 1 05 APR 2012	SUP:
				AMDT: ORIG
				DATED: 12/17/2009

