

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
FOD VORTAC (IAF)	LUGBE/FOD 7.00 DME	062.99 / 7.00	2800	MAP: MANBL/FOD VORTAC 17.65 DME FIX CLIMB TO 2800 THEN LEFT TURN VIA FOD VORTAC R-063 TO FOD VORTAC AND HOLD.
LUGBE/FOD 7.00 DME (IF)	OZXOS/FOD 12.00 DME	062.99 / 5.00 (FOD R-063)	2800	
				ADDITIONAL FLIGHT DATA: HOLD NW, RT, 120.35 INBOUND. CHART FAS OBST: 1478 TOWER 423918N/0935925W CHART: CLARION AWOS-3. FAC CROSSES APPROACH END OF RWY 13.

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **PROFILE STARTS AT FOD VORTAC**
3. FAC 062.99 FAF OZXOS/FOD 12.00 DME DIST FAF TO MAP THLD
4. MIN. ALT FOD VORTAC 2800, LUGBE 2800, OZXOS 2800
8. MSA FROM: FOD VORTAC 270-360 3400, 360-270 2800

MAG VAR: 7E

EPOCH YEAR: 1965

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: NA	X						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1660	1	527	1660	1	527		NA			NA				

NOTES:

CHART NOTE: USE CLARION ALTIMETER SETTING; WHEN NOT RECEIVED USE FORT DODGE ALTIMETER SETTING.

QUALITY
5
CHECKED

CITY AND STATE EAGLE GROVE, IA	ELEVATION: 1133	TDZE:	FACILITY IDENTIFIER: FOD	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME-A, AMDT 2 11 FEB 2010	SUP VOR/DME OR GPS-
	AIRPORT NAME:				A
	EAGLE GROVE MUNI				AMDT 1
					DATE 05/25/1995