

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

**RWY 14, 32, STANDARD
RWY 6, 24, NA- OBSTACLES**

(2) TEXTUAL DP:

**RWY 14 , CLIMB VIA HEADING 142 TO 900 BEFORE PROCEEDING ON COURSE.
RWY 32 , CLIMB VIA HEADING 322 TO 900 BEFORE PROCEEDING ON COURSE.**

(3) TAKEOFF OBSTACLES:

(4) OBSTACLES:

**RWY 14: 559 MSL TOWER 375831.00/0754945.00, 475 MSL TOWER 380145.00/0754504.00
RWY 32: 559 MSL TOWER 375831.00/0754945.00, 475 MSL TOWER 380145.00/0754504.00**

(5) City, State

CRISFIELD, MD

(6) Airport

CRISFIELD MUNI

(7) Effective Date

JAN 23 2003

(8) Amdt. No.

ORIG