

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 18 STANDARD

RWY 36, 400-2 OR STANDARD WITH MINIMUM CLIMB OF 210 FEET PER NM TO 1400.

RWY 2, 8, 11, 20, 26, 29, NA

(2) TEXTUAL DP:

RWY 36, CLIMB VIA HEADING 360 TO 1400 FEET BEFORE TURNING LEFT.

(3) TAKEOFF OBSTACLES:

NOTE: RWY 36 TOWER 2.16 NM FROM DER, 5370 FEET LEFT OF CENTERLINE, 250 FEET AGL/1263 FEET MSL.

(4) OBSTACLES:

RWY 36: 1263 MSL TOWER 355924.00-0964716.00

(5) City, State

CUSHING, OK

(6) Airport

CUSHING MUNI

(7) Effective Date

SEP 4 2003

(8) Amdt. No.

1