

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES																MISSED APPROACH									
FROM				TO				COURSE AND DISTANCE				ALTITUDE		LP: RW04 LNAV: RW04 CLIMB TO 3400 DIRECT CHIEF AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 231.30 INBOUND. CHART FAS OBST: 1315 TOWER 361708N/0923728W CHART FAS OBST: 832 TREE 361638N/0923657W CHART 1052 TREE 361536N/0923825W WAAS CHANNEL # 58239 REFERENCE PATH ID: W04A JUBVU TO RW04: 3.50/55. CHART CIRCLING ICON. CHART KBPK IN PLANVIEW LTP HAE: 170.4 M											
WEDUR (IF/IAF)				JUBVU (FB)				051.05 / 6.79				2800													
JUBVU (FAF)				OVVIX/2.80 NM TO RW04 (FB)				051.15 / 2.83																	
OVVIX/2.80 NM TO RW04				RW04 (MAP) (FO)				051.15 / 2.80																	
RW04 (MAP)				1100 MSL				051.15				3400													
1100 MSL				CHIEF (FO)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW WEDUR, RT, 051.05 INBOUND, 3600 FT. IN LIEU OF PT (IAF) 3. FAC: 051.15 FAF: JUBVU DIST FAF TO MAP: 5.63 THLD: 5.63 4. MIN. ALT: WEDUR 3600, JUBVU 2800, OVVIX/2.80 NM TO RW04 1740 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 0E					EPOCH YEAR: 2020				
MINIMUMS																									
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @															
CATEGORY =====>		A			B			C			D			E											
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA										
LP MDA	1100	1	407	1100	1	407	1100	1 3/8	407		NA														
LNAV MDA	1500	1	807	1500	1 1/4	807	1500	2 1/2	807		NA														
CIRCLING	1500	1	780	1500	1 1/4	780	1500	2 1/2	780		NA														
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: RWY 4 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: CIRCLING NA NW OF RWY 4-22.																									
CITY AND STATE FLIPPIN, AR				ELEVATION: 720 TDZE: 693 AIRPORT NAME: MARION COUNTY RGNL				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 2 MARCH 2017				SUP:											
														AMDT: ORIG											
														DATED 03/12/2009											



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	321/30 CW 141/30 (NOPT) 321/6 CW 141/6	321/6 CW 141/6 WEDUR (IAF) (FB)	3900 3600
2.	141/30 CW 321/30	WEDUR (IF/IAF) (FO)	3600

QUALITY
25
CHECKED

CITY AND STATE FLIPPIN, AR	ELEVATION: 720 AIRPORT NAME: MARION COUNTY RGNL	TDZE: 693	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 2 MARCH 2017	SUP:
					AMDT: ORIG
					DATED: 03/12/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFLP
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	361711.7145N
LTP/FTP LONGITUDE	0923548.7170W
LTP/FTP ELLIPSOIDAL HEIGHT	+01704
FPAP LATITUDE	361807.6150N
FPAP LONGITUDE	0923422.8100W
THRESHOLD CROSSING HEIGHT (TCH)	00055.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.50
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 0E9E756E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+01988
FPAP ORTHOMETRIC HEIGHT	+01988

QUALITY
25
CHECKED

CITY AND STATE FLIPPIN, AR	ELEVATION: 720 AIRPORT NAME: MARION COUNTY RGNL	TDZE: 693 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 2 MARCH 2017	SUP:
				AMDT: ORIG
				DATED: 03/12/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KFLP

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
WEDUR	010	WEDUR	HF	FO		051.1			R			AA 03600		EE A
	010	WEDUR	IF	FB								AA 03600		E I
	020	JUBVU	TF	FB	1.0	051.1						AA 02800		E F
	021	OVVIX	TF	FB	0.3	051.2		3.50				AA 01740 GS 01748		E S
	030	RW04	TF	FO	0.3	051.2		3.50				AT 00707		GY M
	040		CA	FB		051.2						AA 01100		M
	050	CHIEF	DF	FO	1.0							AA 03400		EY
	060	CHIEF	HM	FO		231.3			R			AA 03400		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
CHIEF	N362524.18	W0922310.30
JUBVU	N361339.60	W0924114.14
OVVIX	N361526.27	W0923830.61
WEDUR	N360923.32	W0924745.67

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW04	N361711.71	W0923548.72	00652	55

QUALITY
25
CHECKED

CITY AND STATE FLIPPIN, AR	ELEVATION: 720 TDZE: 693	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1 2 MARCH 2017	SUP:
	AIRPORT NAME: MARION COUNTY RGNL			AMDT: ORIG
				DATED: 03/12/2009