

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CHIEF (IF/IAF)	RAJFA (TF) (FB) (RNP 1.00)	231.30 / 6.81	2800	LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 3600 DIRECT WEDUR AND HOLD.
RAJFA (FAF)	RW22 (MAP) (TF) (FO) (RNP 0.30)	231.25 / 5.46		
RW22 (MAP)	1022 MSL	231.25		
1022 MSL	WEDUR (DF) (FO) (RNP 1.00)		3600	ADDITIONAL FLIGHT DATA: HOLD SW, RT, 051.05 INBOUND. FAS OBST: 940 AAO 361947N/0923149W DISTANCE TO THLD FROM 302 HAT: 0.67 NM. WAAS CHANNEL # 90539 REFERENCE PATH ID: W22A CHART CIRCLING ICON. CHART KBPK IN PLANVIEW LTP HAE: 190.9 M

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD NE CHIEF, RT, 231.30 INBOUND, 3400 FT. IN LIEU OF PT (IAF)
3. FAC: 231.25 FAF: RAJFA DIST FAF TO MAP: 5.46 THLD: 5.46
4. MIN. ALT: **CHIEF 3400, RAJFA 2800**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 2800 GS ALT AT: RAJFA 2800 OM: MM: IM:
7. GS ANGLE: 3.50 TCH: 52.0 34:1 IS NOT CLEAR
8. MSA FROM:


MAG VAR: 0E EPOCH YEAR: 2020

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1022	1	302	1022	1	302	1022	1	302		NA				
LNAV/VNAV DA	1169	1 3/8	449	1169	1 3/8	449	1169	1 3/8	449		NA				
LNAV MDA	1320	1	600	1320	1	600	1320	1 3/4	600		NA				
CIRCLING	1320	1	600	1320	1	600	1360	1 3/4	640		NA				

- NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -13C (9F) OR ABOVE 54C (130F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: CIRCLING NA NW OF RWY 4-22.
 CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CITY AND STATE FLIPPIN, AR	ELEVATION: 720 TDZE: 720 AIRPORT NAME: MARION COUNTY RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1 2 MARCH 2017	SUP: 4 AMDT ORIG DATED 03/12/2009
--------------------------------------	--	-------------------------------------	---	--



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA	FROM	TO	ALT
1.	141/30 CW 321/30 (NOPT)	CHIEF (IF/IAF) (FB)	3400
	321/30 CW 141/30	CHIEF (IF/IAF) (FO)	3400

CITY AND STATE FLIPPIN, AR	ELEVATION: 720 AIRPORT NAME: MARION COUNTY RGNL	TDZE: 720	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1 2 MARCH 2017	SUP: 4
					AMDT: CHECKED ORIG
					DATED: 03/12/2009

QUALITY

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFLP
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	361742.6975N
LTP/FTP LONGITUDE	0923501.1140W
LTP/FTP ELLIPSOIDAL HEIGHT	+01909
FPAP LATITUDE	361646.7805N
FPAP LONGITUDE	0923626.9965W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.50
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 363E8CCD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+02193
FPAP ORTHOMETRIC HEIGHT	+02193

CITY AND STATE FLIPPIN, AR	ELEVATION: 720	TDZE: 720	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1 2 MARCH 2017	SUP: 4
	AIRPORT NAME: MARION COUNTY RGNL				AMDT: 0
					DATED: 03/12/2009

QUALITY
4
ORIG
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KFLP

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
CHIEF	010	CHIEF	HF	FO		231.3			R			AA 03400		EE A
	010	CHIEF	IF	FB								AA 03400		E I
	020	RAJFA	TF	FB	1.0	231.3						AA 02800		E F
	030	RW22	TF	FO	0.3	231.3		3.50				AT 00772		GY M
	040		CA	FB		231.3						AA 01022		M
	050	WEDUR	DF	FO								AA 03600		EY
060	WEDUR	HM	FO			051.1		R			AA 03600		EE	

POINTS

POINT NAME	LATITUDE	LONGITUDE
CHIEF	N362524.18	W0922310.30
RAJFA	N362108.07	W0922945.17
WEDUR	N360923.32	W0924745.67

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW22	N361742.70	W0923501.11	00720	52



CITY AND STATE FLIPPIN, AR	ELEVATION: 720 TDZE: 720	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 1 2 MARCH 2017	SUP:
	AIRPORT NAME: MARION COUNTY RGNL			AMDT: ORIG
				DATED: 03/12/2009