

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SHOW LOW, AZ	SHOW LOW RGNL	19 JULY 2018	2

TAKEOFF MINIMUMS:

RWY 4, 7, 22, 25: STANDARD

TEXTUAL DEPARTURE PROCEDURES:

RWY 4: CLIMBING LEFT TURN HEADING 360.00 TO 7800 BEFORE PROCEEDING ON COURSE.

RWY 7: CLIMBING LEFT TURN HEADING 360.00 TO 8100 BEFORE PROCEEDING ON COURSE.

RWY 22: CLIMBING RIGHT TURN HEADING 255.00 TO 7700 BEFORE PROCEEDING ON COURSE.

RWY 25: CLIMB ON HEADING 245.99 TO 7600 BEFORE PROCEEDING ON COURSE.

VISUAL CLIMB OVER AIRPORT:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 04: SIGN, BUILDING, FENCE, POLE BEGINNING 44 FT FROM DER, 183 FT RIGHT OF CENTERLINE, UP TO 6 FT AGL/6406 FT MSL. TREE 88 FT FROM DER, 488 FT LEFT OF CENTERLINE, 6411 FT MSL.

TREES BEGINNING 185 FT FROM DER, 428 FT LEFT OF CENTERLINE, UP TO 6417 FT MSL.

POLE 240 FT FROM DER, 222 FT RIGHT OF CENTERLINE, 16 FT AGL/6411 FT MSL.

NOTE: RWY 07: GENERAL UTILITY 39 FT FROM DER, 92 FT RIGHT OF CENTERLINE, 19 FT AGL/6402 FT MSL.

GENERAL UTILITY 40 FT FROM DER, 88 FT LEFT OF CENTERLINE, 20 FT AGL/6402 FT MSL.

NOTE: RWY 22: TREE 94 FT FROM DER, 197 FT LEFT OF CENTERLINE, 6424 FT MSL.

TREES BEGINNING 133 FT FROM DER, 87 FT RIGHT OF CENTERLINE, UP TO 6420 FT MSL.

POLE 397 FT FROM DER, 141 FT LEFT OF CENTERLINE, 23 FT AGL/6426 FT MSL.

POLE 469 FT FROM DER, 166 FT LEFT OF CENTERLINE, 27 FT AGL/6430 FT MSL.

BUILDING 677 FT FROM DER, 423 FT LEFT OF CENTERLINE, 24 FT AGL/6433 FT MSL.

ELEVATOR, TANK, POLE BEGINNING 1191 FT FROM DER, 5 FT LEFT OF CENTERLINE, UP TO 63 FT AGL/6496 FT MSL.

NOTE: RWY 25: POLE 10 FT FROM DER, 29 FT RIGHT OF CENTERLINE, 18 FT AGL/6401 FT MSL.

POLE 640 FT FROM DER, 310 FT RIGHT OF CENTERLINE, 6418 FT MSL.

POLE 644 FT FROM DER, 307 FT RIGHT OF CENTERLINE, 37 FT AGL/6419 FT MSL.

POLE BEGINNING 704 FT FROM DER, 677 FT LEFT OF CENTERLINE, UP TO 53 FT AGL/6437 FT MSL.

POLE, CATENARY BEGINNING 726 FT FROM DER, 3 FT LEFT OF CENTERLINE, UP TO 54 FT AGL/6438 FT MSL.

POLE 760 FT FROM DER, 158 FT RIGHT OF CENTERLINE, 47 FT AGL/6430 FT MSL.

POLE 763 FT FROM DER, 159 FT RIGHT OF CENTERLINE, 49 FT AGL/6432 FT MSL.

POLE, CATENARY BEGINNING 764 FT FROM DER, 77 FT RIGHT OF CENTERLINE, UP TO 54 FT AGL/6437 FT MSL.

POLE BEGINNING 842 FT FROM DER, 317 FT RIGHT OF CENTERLINE, UP TO 57 FT AGL/6438 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT:

RWY 4, 25: 11542 FT MSL AAO 335618.00N/1093618.00W.

RWY 7, 22: 7852 FT MSL TOWER 341220.00N/1095628.00W.

REMARKS:

FLIGHT INSPECTED BY:

Digitally signed by

DEZ SILAGYI

KENNETH E JACK

May 25, 2018

OFFICE SYMBOL:

FICO

DATE:

5/24/18

DEVELOPED BY:

Digitally signed by

DEANNA M FIELDS

DEANNA M. FIELDS

Apr 11, 2018

OFFICE SYMBOL:

AJV-5421

DATE:

03/21/2018

APPROVED BY:

Digitally signed by

DEZ SILAGYI

JULIE MORGAN

May 25, 2018

OFFICE SYMBOL:

AJV-5420

DATE:



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
SHOW LOW, AZ	SHOW LOW RGNL	19 JULY 2018	2

REQUIRED EFFECTIVE DATE:
ROUTINE

COORDINATED WITH:

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:
AMGR, ZAB

CHANGES - REASONS:

1. ALL REFERENCE TO RWY 3, 6, 21 AND 24 CHANGED TO RWY 4, 7, 22, AND 25 - MAGVAR CHANGED FROM E13/1985 TO E10/2020.
2. TEXTUAL DEPARTURE PROCEDURES - RWY 25: HEADING CHANGED FROM 242.99 TO 245.99 - MAGVAR CHANGED FROM E13/1985 TO E10/2020.
3. UPDATED LOW CLOSE IN OBSTACLES - NEW SURVEY.
4. RWY 7 AND 22 OBSTACLE MANDATING ODP ROUTE DEVELOPMENT CHANGED FROM 11542 FT MSL AAO 335618.00N/1093618.00W TO 7852 FT MSL TOWER 341220.00N/1095628.00W.

