

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
DILLON, MT	DILLON	27 JUNE 2013	AMDT 3

TAKEOFF MINIMUMS:

RWY 4, 35 STANDARD
RWY 17, STANDARD WITH MINIMUM CLIMB OF 219 FT PER NM TO 6400 OR 3700 – 3 FOR CLIMB IN VISUAL CONDITIONS.
RWY 22, 3700 – 3 FOR CLIMB IN VISUAL CONDITIONS.
CHART NOTE: RWY 4, 35 DME REQUIRED.

TEXTUAL DEPARTURE PROCEDURES:

NOTE: RWY 4, CLIMBING LEFT TURN THENCE...
NOTE: RWY 17, CLIMBING RIGHT TURN HEADING 042.00 THENCE...OR FOR CLIMB IN VISUAL CONDITIONS CROSS DILLON AIRPORT AT OR ABOVE 9000 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.
NOTE: RWY 22, FOR CLIMB IN VISUAL CONDITIONS CROSS DILLON AIRPORT AT OR ABOVE 9000 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.
NOTE: RWY 35, CLIMBING RIGHT TURN THENCE...

....CLIMB TO 8900 ON DLN R-005 TO YARUP/DLN 19.00 DME FIX. AIRCRAFT DEPARTING NORTH ON V21 CONTINUE CLIMB TO MEA AND PROCEED ON COURSE. AIRCRAFT DEPARTING SOUTH ON V121 AND V21-257, CLIMBING LEFT TURN HEADING 140.00 TO INTERCEPT DLN R-005 SOUTHBOUND, CROSS DLN VOR/DME AT OR ABOVE 10000 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 4, LIGHT 9 FT FROM DER, 19 FT RIGHT OF CENTERLINE, 3 FT AGL/5229 FT MSL. FENCE 96 FT FROM DER, 251 FT RIGHT OF CENTERLINE, 13 FT AGL/5234 FT MSL. VEHICLES ON ROADWAY BEGINNING 211 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/5246 FT MSL.

NOTE: RWY 17, LIGHT 7 FT FROM DER, 27 FT LEFT OF CENTERLINE, 3 FT AGL/5247 FT MSL. VEHICLES ON ROADWAY BEGINNING 13 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/5262 FT MSL. POLE 850FT FROM DER, 507 FT LEFT OF CENTERLINE, 33 FT AGL/5274 FT MSL.

NOTE: RWY 22, LIGHT 10 FT FROM DER, 20 FT RIGHT OF CENTERLINE, 2 FT AGL/5223 FT MSL. VEHICLES ON ROADWAY BEGINNING 13 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/5236 FT MSL.

NOTE: RWY 35, VEHICLES ON ROADWAY BEGINNING 6 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/5170 FT MSL. LIGHT 9 FT FROM DER, 27 FT LEFT OF CENTERLINE, 2 FT AGL/5158 FT MSL.

CONTROLLING OBSTACLES:

RWY 17: 6056 FT MSL AAO, 451421.13N/1124006.27W.
RWY 17, 22 (VCOA): 11354 FT MSL AAO, 452848.10N/1125753.30W; 6076 FT MSL AAO, 451353.38N/1122635.83W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 4, 35 - 8564 FT MSL AAO 453149.20N/1123730.40W. RWY 17 – 8655 FT MSL AAO 450709.00N/1122800.00W.

3/1/14
0400Z
0400Z