

QUALITY
9
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

*LNAV ONLY

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE BLYTHEVILLE MUNI ALTIMETER SETTING; INCREASE ALL DA 47 FEET AND ALL MDA 60 FEET; INCREASE LNAV/VNAV VISIBILITY ALL CATS 1/8 MILE, LNAV CAT C AND D VISIBILITY 1/8 MILE, AND CIRCLING CAT D VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

CHART NOTE: RWY 2 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	288/30 CW 108/30 (NOPT)	COSAD (IF/IAF) (FB)	2500
2.	108/30 CW 288/30	COSAD (IF/IAF) (FO)	2500

QUALITY
9
CHECKED

CITY AND STATE

KENNETT, MO

ELEVATION: 262

THRE: 259

AIRPORT NAME:

KENNETT MEMORIAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 2, AMDT 1

6 MARCH 2014

SUP:

AMDT: ORIG

DATED: 04/13/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTKX
RUNWAY	RW02
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W02A
LTP/FTP LATITUDE	361301.9665N
LTP/FTP LONGITUDE	0900226.0400W
LTP/FTP ELLIPSOIDAL HEIGHT	+00504
FPAP LATITUDE	361426.8900N
FPAP LONGITUDE	0900152.2600W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

50534C91

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+00788
FPAP ORTHOMETRIC HEIGHT	+00788

QUALITY
9
CHECKED

CITY AND STATE

KENNETT, MO

ELEVATION: 262

THRE: 259

AIRPORT NAME:

KENNETT MEMORIAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 2, AMDT 1

6 MARCH 2014

SUP:

AMDT: ORIG

DATED: 04/13/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KTKXK3FR02	ACOSAD	010COSADK3EA0EE	AL	HF			01780040	+	02500	18000		A	JS
SUSAP KTKXK3FR02	R	010COSADK3EA0E	I	IF				+	02500	18000		A	JS
SUSAP KTKXK3FR02	R	020HESLUK3EA1E	F	051TF			01780061	+	01900			A	JS
SUSAP KTKXK3FR02	R	020HESLUK3EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KTKXK3FR02	R	021ZISGOK3EA0E	S	031TF			01780030	V	0092000935		-300	A	JS
SUSAP KTKXK3FR02	R	030RW02 K3PGOGY	M	031TF			01780020		00299		-300	A	JS
SUSAP KTKXK3FR02	R	040	0	M	CA		0178	+	00509			A	JS
SUSAP KTKXK3FR02	R	050OGVIEK3EA0EY		DF				+	02500			A	JS
SUSAP KTKXK3FR02	R	060OGVIEK3EA0EE	R	HM			19790040	+	02500			A	JS

[illegible][illegible]

QUALITY
9
CHECKED

CITY AND STATE KENNETT, MO	ELEVATION: 262 THRE: 259 AIRPORT NAME: KENNETT MEMORIAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 2, AMDT 1 6 MARCH 2014	SUP:
				AMDT: ORIG
				DATED: 04/13/2006

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	COSAD	COSAD	010	IAF	HF	L	FO		017.8 (017.8T)	004.0	AA 02500	
		COSAD	010	FACF	IF		FB				AA 02500	
		HESLU	020	FAF	TF		FB	0.5	017.8 (017.8T)	006.1	AA 01900	
		ZISGO	021	SDF	TF		FB	0.3	017.8 (017.8T)	003.0	AA 00920	GS 00935
		RW02	030	MAP	TF		FO	0.3	017.8 (017.8T)	002.0	AT 00299	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		017.8 (017.8T)		AA 00509	
	OGVIE	050		DF		FO				AA 02500	
	OGVIE	060		HM	R	FO		197.9 (197.9T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	COSAD	N360225.37	W0900638.58	N3602.423	W09006.643
	HESLU	N360814.35	W0900420.29	N3608.239	W09004.338
	OGVIE	N362425.43	W0895753.46	N3624.424	W08957.891
	ZISGO	N361107.59	W0900311.50	N3611.127	W09003.192
	RW02	N361301.97	W0900226.04	N3613.033	W09002.434

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW02	00259	40

QUALITY
9
CHECKED

CITY AND STATE KENNETT, MO	ELEVATION: 262	THRE: 259	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: KENNETT MEMORIAL		RNAV	RNAV (GPS) RWY 2, AMDT 1	AMDT: ORIG
				6 MARCH 2014	DATED: 04/13/2006