

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 1200 THEN CLIMBING RIGHT TURN TO 3700 DIRECT JOTAV AND HOLD, CONTINUE CLIMB IN HOLD TO 3700. ADDITIONAL FLIGHT DATA: HOLD W, RT, 111.00 INBOUND. CHART FAS OBST: 818 TREE 333636N/0860039W CHART R-2101, R-2102 A, B, C. DISTANCE TO THLD FROM 292 HAT: 0.77 NM. CHART VDP AT 1.58 NM TO RW22* *LNAV ONLY. WAAS CHANNEL # 93720 REFERENCE PATH ID: W22A CHART CIRCLING ICON. LTP HAE: 132.2 M						
ZEKNE (IF/IAF)		KOZJE (TF) (FB) (RNP 1.00)			218.45 / 8.76			2400								
KOZJE (FAF)		SOVPE/3.00 NM TO RW22 (TF) (FB) (RNP 0.30)			218.42 / 2.74											
SOVPE/3.00 NM TO RW04		RW22 (MAP) (TF) (FO) (RNP 0.30)			218.42 / 3.00											
RW22 (MAP)		1200 MSL (CA)			218.42			1200								
1200 MSL		JOTAV (DF) (FO) (RNP 1.00)						3700								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE ZEKNE, RT, 218.45 INBOUND, 3100 FT. IN LIEU OF PT (IAF) 3. FAC: 218.42 FAF: KOZJE DIST FAF TO MAP: 5.74 THLD: 5.74 4. MIN. ALT: ZEKNE 3100, KOZJE 2400, SOVPE/3.00 NM TO RW22 1520* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2400 GS ALT AT: KOZJE 2400 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS NOT CLEAR 8. MSA FROM: _____											MAG VAR: 3W		EPOCH YEAR: 2010			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A X									
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	821	1	292	821	1	292	821	1	292	821	1	292				
LNAV/VNAV DA	1040	1 3/4	511	1040	1 3/4	511	1040	1 3/4	511	1040	1 3/4	511				
LNAV MDA	1080	1	551	1080	1	551	1080	1 5/8	551	1080	1 5/8	551				
CIRCLING	1140	1	611	1180	1	651	1380	2 1/2	851	1500	3	971				
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING ANNISTON ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VDP NA WITH ANNISTON ALTIMETER SETTING. (CONTINUED ON PAGE 2)																
CITY AND STATE TALLADEGA, AL				ELEVATION: 529 TDZE: 529 AIRPORT NAME: TALLADEGA MUNI			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 2 1 FEBRUARY 2018				SUP: AMDT: 1B DATED 06/26/2014			



**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANNISTON ALTIMETER SETTING AND INCREASE

LPV DA TO 856, LNAV/VNAV DA TO 1075, AND ALL MDA 40 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS

VISIBILITY AND LNAV CATS C/D VISIBILITY 1/8 MILE. INCREASE CIRCLING CAT C VISIBILITY 1/4 SM.

CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	128/30 CW 308/30 (NOPT)	128/5 CW 308/5	3700
2.	128/5 CW 308/5	ZEKNE (IF/IAF) (FB)	3100
3.	308/30 CW 128/30	308/5 CW 128/5	4000
4.	308/5 CW 128/5	ZEKNE (IF/IAF) (FO)	3100

QUALITY
18
CHECKED

CITY AND STATE

TALLADEGA, AL

ELEVATION: 529

TDZE: 529

AIRPORT NAME:

TALLADEGA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 22, AMDT 2

1 FEBRUARY 2018

SUP:

AMDT: 1B

DATED: 06/26/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KASN
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	333434.5400N
LTP/FTP LONGITUDE	0860243.6900W
LTP/FTP ELLIPSOIDAL HEIGHT	+01322
FPAP LATITUDE	333321.7600N
FPAP LONGITUDE	0860345.4200W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0912
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 5AF2C641

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+01610
FPAP ORTHOMETRIC HEIGHT	+01610

QUALITY
18
CHECKED

CITY AND STATE TALLADEGA, AL	ELEVATION: 529 TDZE: 529 AIRPORT NAME: TALLADEGA MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 2 1 FEBRUARY 2018	SUP:
				AMDT: 1B
				DATED: 06/26/2014