

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MISSED APPROACH		
HEGMA/ABQ 10.00 DME (IF)	ABQ VORTAC (NOPT)	075.35 / 10.00	8000	MAP: 9.76 NM AFTER ABQ VORTAC OR AT MACOL/ABQ 9.76 DME FIX		
				CLIMB TO 5800 THEN CLIMBING RIGHT TURN TO 8000 DIRECT ABQ VORTAC AND HOLD.		
				ADDITIONAL FLIGHT DATA: HOLD W, LT, 077.00 INBOUND. CHART FAS OBST: 5450 BLDG 350303N/1063717W 6177 AAO 350336N/1064857W CHART VDP AT 8.70 DME DISTANCE VDP TO THLD 1.05 NM. CHART CIRCLING ICON. CHART ASR CHART ABQ R-255 AT HEGMA/10.00 DME.		

- PT R SIDE OF COURSE 256.76 OUTBOUND 8200 FT WITHIN 15 MILES OF ABQ VORTAC (IAF)
-
- FAC 076.76 FAF ABQ VORTAC DIST FAF TO MAP 9.76 THLD 9.76
- MIN. ALT ABQ VORTAC 8000, EYECE/ABQ 6.06 DME 6380
- MSA FROM: ABQ VORTAC 020-110 11900, 110-200 10900, 200-020 9100

MAG VAR: 13E EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE:	N A @								
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-08	6380	4000	1060	6380	5500	1060	6380	2 1/2	1060	6380	2 1/2	1060	6380	2 1/2	1060	
CIRCLING	6380	1 1/4	1025	6380	1 1/2	1025	6380	3	1025	6460	3	1105	7460	3	2105	

EYECE FIX MINIMUMS

S-08	5700	2400	380	5700	2400	380	5700	4000	380	5700	4000	380	5700	4000	380
CIRCLING	5840	1	485	5920	1	565	5940	1 1/2	585	6460	3	1105	7460	3	2105

NOTES:

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT HEGMA ON V12 EASTBOUND.
 CHART NOTE: EYECE FIX MINIMUMS: FOR INOPERATIVE ALS, INCREASE S-08 CAT C/D/E VISIBILITY TO RVR 5500.
 CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-08 CAT E VISIBILITY TO 3 SM.
 CHART NOTE: CIRCLING CAT E NOT AUTHORIZED SE OF RWY 3-21 AND NE OF RWY 12-30.

@ CAT A, B 1100-2, CAT C 1100-3, CAT D 1200-3, CAT E 2200-3

CITY AND STATE ALBUQUERQUE, NM	ELEVATION: 5355 TDZE: 5320 AIRPORT NAME: ALBUQUERQUE INTL SUNPORT	FACILITY IDENTIFIER: ABQ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 8, AMDT 21 2 MARCH 2017	SUP VOR OR TACAN RWY 8 AMDT 4 20A DATE CHECKED 03/30/2007
-----------------------------------	---	-----------------------------	--	--

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

(This area is intentionally left blank for the VOR Standard Instrument Approach Procedure.)

CITY AND STATE ALBUQUERQUE, NM	ELEVATION: 5355 TDZE: 5320 AIRPORT NAME: ALBUQUERQUE INTL SUNPORT	FACILITY IDENTIFIER: ABQ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 8, AMDT 21 2 MARCH 2017	SUP: VOR OR TACAN
				RWY 8
				AMDT: 4 20A
DATED: 08/30/2007				