

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW17 CLIMB TO 2000 DIRECT EDUYA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 349.48 INBOUND. FAS OBST: 219 AAO 301436N/0905650W CHART: 514 TOWER 301515N/0905638W DISTANCE TO THLD FROM 394 HAT: 1.11 NM. WAAS CHANNEL # 78429 REFERENCE PATH ID: W17A CHART BATON ROUGE ASOS. LTP HAE: -22.9 M									
LSU VORTAC (IAF)		AYUYE (NOPT) (TF) (FB) (RNP 1.00)		111.86 / 18.20				2000											
DILLS (IAF)		AYUYE (NOPT) (TF) (FB) (RNP 1.00)		185.21 / 8.54				2000											
AYUYE (IF/IAF)		FENPA (TF) (FB) (RNP 1.00)		169.44 / 6.01				1700											
FENPA (FAF)		RW17 (MAP) (TF) (FO) (RNP 0.30)		169.45 / 5.10															
RW17 (MAP)		407 MSL		169.45				2000											
407 MSL		EDUYA (DF) (FO) (RNP 1.00)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N AYUYE, RT, 169.44 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: 169.45 FAF: FENPA DIST FAF TO MAP: 5.10 THLD: 5.10 4. MIN. ALT: AYUYE 2000, FENPA 1700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1700 GS ALT AT: FENPA 1700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM: RW17 3100																MAG VAR: 2E		EPOCH YEAR: 1995	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X									
CATEGORY ==>		A		B		C		D		E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	407	1 3/8	394	407	1 3/8	394	407	1 3/8	394	407	1 3/8	394							
LNAV/VNAV DA	471	1 5/8	458	471	1 5/8	458	471	1 5/8	458	471	1 5/8	458							
LNAV MDA	540	1	527	540	1	527	540	1 1/2	527	540	1 1/2	527							
CIRCLING	540	1	526	580	1	566	620	1 3/4	606	640	2	626							
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT DILLS ON V566 NORTHWEST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON LSU VORTAC AIRWAY RADIALS 041 CW 106. (CONTINUED ON PAGE 2)																			
CITY AND STATE		ELEVATION: 14 TDZE: 13		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		QUALITY 19 CHECKED							
GONZALES, LA		AIRPORT NAME:		LOUISIANA RGNL		RNAV (GPS) RWY 17, AMDT 1C				AMDT: 1B									
						2 MARCH 2017				DATED 04/30/2015									

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: USE BATON ROUGE ALTIMETER SETTING.

CHART NOTE: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CITY AND STATE
GONZALES, LA

ELEVATION: 14 TDZE: 13
AIRPORT NAME:
LOUISIANA RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, AMDT 1C
2 MARCH 2017

SUP:
AMDT: 1B
DATED: 04/30/2015

QUALITY
19
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KREG
RUNWAY	RW17
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17A
LTP/FTP LATITUDE	301041.4085N
LTP/FTP LONGITUDE	0905629.6305W
LTP/FTP ELLIPSOIDAL HEIGHT	-00229
FPAP LATITUDE	300913.0900N
FPAP LONGITUDE	0905614.3700W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 F4A0B337

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00038
FPAP ORTHOMETRIC HEIGHT	+00038

CITY AND STATE
GONZALES, LA

ELEVATION: 14 TDZE: 13
AIRPORT NAME:
LOUISIANA RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, AMDT 1C
2 MARCH 2017

SUP: **19**
AMDT: **1B**
DATED: **04/30/2015**

QUALITY
19
CHECKED