## U.S. DEPARTMENT of TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

## TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

nautical miles. Visibilities are in statute miles or feet RVR unless otherwise	is and autitudes are in feet, MSL. Affitudes are minimum affitudes unless otherwise indicated. Ceilings are in se indicated.	eet above airport elevation. Dis	stances are in
(1) TAKEOFF MINIMUMS: RWY 36: STANDARD			
RWY 18: 400-1 OR STANDARD WITH MINIMUM	CLIMB OF 335 FEET PER NM TO 1600		
(2) DEPARTURE PROCEDURE:			
(3) TAKEOFF OBSTACLE NOTES: NOTE: RWY 18, TOWERS 6684 FEET FROM DER, 2072 FEET LEFT OF CENTERLINE, 140 FEET AGL/1340 FEET MSL.			
NOIE: NWY 10, IOWENS 0004 FEET FROM DE	n, 2012 FEET LEFT OF CENTERLINE, 140 FEET AGL/1340 FEET MSL.		
(4) CONTROLLING OBSTACLES: RWY 18: 1340 MSL TOWERS 451527.00/0922159.00-OIS 35' ABOVE DER ELEVATION.			
			Las A. V. Si
(5) City, State  AMERY, WISCONSIN	(6) Airport  AMERY MUNI	(7) Effective Date MAR 1 7 2005	(8) Amdt. No. 1