

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 2600 DIRECT GOKDE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 002.84 INBOUND. CHART FAS OBST: 412 TREE 310157N/0872624W. DISTANCE TO THLD FROM 327 HAT: 0.87 NM. WAAS CHANNEL # 40031 REFERENCE PATH ID: W18A CHART CIRCLING ICON. CHART BREWTON AWOS-3. LTP HAE: 58.3 M						
FEVIB (IF/IAF)		HELUD (TF) (FB) (RNP 1.00)			182.84 / 7.00			2000								
HELUD (FAF)		JEDAM/2.60 NM TO RW18 (TF) (FB) (RNP 0.30)			182.84 / 2.63											
JEDAM/2.60 NM TO RW18		RW18 (MAP) (TF) (FO) (RNP 0.30)			182.84 / 2.60											
RW18 (MAP)		613 MSL (CA)			182.84											
613 MSL		GOKDE (DF) (FO) (RNP 1.00)						2600								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N FEVIB, RT, 182.84 INBOUND, 2600 FT. IN LIEU OF PT (IAF) 3. FAC: 182.84 FAF: HELUD DIST FAF TO MAP: 5.23 THLD: 5.23 4. MIN. ALT: FEVIB 2600, HELUD 2000, JEDAM/2.60 NM TO RW18 1160* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2000 GS ALT AT: HELUD 2000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 52.0 34:1 IS NOT CLEAR 8. MSA FROM: _____											MAG VAR: 3W		EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A ☒ X									
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	613	1	327	613	1	327	613	1	327	613	1	327				
LNAV/VNAV DA	653	1	367	653	1	367	653	1	367	653	1	367				
LNAV MDA	740	1	454	740	1	454	740	1 3/8	454	740	1 3/8	454				
CIRCLING	880	1	594	880	1	594	980	2	694	1000	2 1/4	714				
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 286 TDZE: 286			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP:		
ATMORE, AL		AIRPORT NAME:						RNAV (GPS) RWY 18, AMDT 2						AMDT: 1A		
		ATMORE MUNI						1 FEBRUARY 2018						DATED 05/29/2014		

QUALITY
16
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

*LNAV ONLY

CHART NOTE: USE BREWTON ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	093/30 CW 273/30 (NOPT)	FEVIB (IF/IAF) (FB)	2600
2.	273/30 CW 093/30	FEVIB (IF/IAF) (FO)	2600

QUALITY
16
CHECKED

CITY AND STATE
ATMORE, AL

ELEVATION: 286 TDZE: 286
AIRPORT NAME:
ATMORE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, AMDT 2
1 FEBRUARY 2018

SUP:
AMDT: 1A
DATED: 05/29/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	0R1
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	310122.8855N
LTP/FTP LONGITUDE	0872648.4000W
LTP/FTP ELLIPSOIDAL HEIGHT	+00583
FPAP LATITUDE	305953.5855N
FPAP LONGITUDE	0872648.1140W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1232
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 799D1563

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00863
FPAP ORTHOMETRIC HEIGHT	+00863

QUALITY
16
CHECKED

CITY AND STATE ATMORE, AL	ELEVATION: 286 AIRPORT NAME: ATMORE MUNI	TDZE: 286 ATMORE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 2 1 FEBRUARY 2018	SUP:
					AMDT: 1A
					DATED: 05/29/2014