

INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
CIMGO (IAF)(40E)(43A)	DETEY (TF)(FB)(40E)(41E)	346.47/6.45	5900	LNAV: RW25			
DETEY (IF)(40E)(43I)	HUMIK (TF)(FB)(40E)(43F)	266.51/7.00	4800				
HUMIK (FAF)(43E)(43F)	JUKAN (TF)(FB)(40E)(42S)	266.30/6.30	2740	CLIMB TO 8000 DIRECT GEYET AND VIA 261.16 TRACK TO EGAXE AND HOLD, CONTINUE CLIMB-IN-HOLD TO 8000.			
JUKAN (40E)(42S)	RW25 (TF)(FO)(40G)(41Y)(43M)	266.30/3.70					
RW25 (MAP)(40G)(41Y)(43M)	2039 MSL (CA)(42M)	266.30		ADDITIONAL FLIGHT DATA: HOLD W, LT, 093.55 INBOUND** CHART FAS OBST: 1899 AAO 631857N/1425442W CHART 2499 AAO 631345N/1423848W. CHART NORTHWAY ASOS, 135.40 FREQUENCY. ROUTE TYPE: A, P ROUTE TYPE QUALIFIER 2: C			
2039 MSL	GEYET (DF)(FB)(40E)						
GEYET (40E)	EGAXE (TF)(FO)(40E)(41E)(43H)	261.16/16.28	8000				

1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
 2. PROFILE STARTS AT DETEY
 3. FAC: 266.30 FAF: HUMIK DIST FAF TO MAP: 10.00 THLD: _____
 4. MIN. ALT: DETEY 5900, HUMIK 4800, JUKAN/3.70 NM TO RW25 (40E)(42S) 2740
 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
 7. GS ANGLE: _____ TCH: _____
 8. MSA FROM: RW25 8700

MAG VAR: 29E EPOCH YEAR: 85

MINIMUMS																	
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		X						
CATEGORY	A			B			C			D			E				
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA		
CIRCLING	2580	1 1/4	941	2580	1 1/4	941			NA			NA					

NOTES:
 CHART NOTES: USE NORTH WAY ALTIMETER SETTING
 DME/DME RNP-0.3 NA.

CITY AND STATE TOK, AK	ELEVATION: 1636 TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: AUG 30 2007 RNAV (GPS) - A, ORIG-A	SUP: RNAV (GPS)-A
	AIRPORT NAME: TOK JUNCTION			AMDT: ORIG
	DATED: 11/23/2006			