

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: MKT VOR/DME	
MKT VOR/DME	ERIXN INT/6.00 DME	160.01 / 6.00	2700	CLIMB TO 2300 THEN CLIMBING RIGHT TURN TO 2700 DIRECT MKT VOR/DME AND HOLD.	
				ADDITIONAL FLIGHT DATA: HOLD S, RT, 340.01 INBOUND. CHART FAS OBST: 1105 TREE 441224N/0935438W CHART VDP AT 1.20 DME; DISTANCE VDP TO THLD 1.04 MILES. FAC CROSSES RWY C/L EXTENDED 2929 FROM THLD.	

1. PT L SIDE OF COURSE 160.01 OUTBOUND 2700 FT WITHIN 10 MILES OF ERIXN (IAF)
 2. _____
 3. FAC 340.01 FAF ERIXN INT/6.00 DME DIST FAF TO MAP _____ THLD 5.85
 4. MIN. ALT ERIXN 2600, LUCET/MKT 2.50 DME 1520*
 8. MSA FROM: MKT VOR/DME 3200

MAG VAR: 7E EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-33	1520	1/2	499	1520	1/2	499	1520	3/4	499	1520	1	499			
CIRCLING	1520	1	499	1520	1	499	1520	1 1/2	499	1580	2	559			

LUCET FIX MINIMUMS

S-33	1400	1/2	379	1400	1/2	379	1400	1/2	379	1400	1	379			
CIRCLING	1440	1	419	1480	1	459	1480	1 1/2	459	1580	2	559			

NOTES:

*1580 WHEN USING WASECA ALTIMETER SETTING.
 CHART NOTE: VDP NA WHEN USING WASECA ALTIMETER SETTING.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE WASECA ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, AND INCREASE S-33 CATS C AND D VISIBILITY 1/4 MILE AND LUCET FIX MINIMUMS S-33 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE MANKATO, MN	ELEVATION: 1021 TDZE: 1021	FACILITY IDENTIFIER: MKT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 33, AMDT 8 24 SEP 2009	SUP VOR OR GPS RWY 33
	AIRPORT NAME: MANKATO RGNL			AMDT 7
				DATE 07/10/2003

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CAT C 1/4 MILE.

CHART NOTE: FOR INOPERATIVE MALSR INCREASE LUCET FIX MINIMUMS CAT D VISIBILITY 1/4 MILE.

QUALITY
 &
 CHECKED

CITY AND STATE MANKATO, MN	ELEVATION: 1021 TDZE: 1021 AIRPORT NAME: MANKATO RGNL	FACILITY IDENTIFIER: MKT	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 33, AMDT 8 24 SEP 2009	SUP: VOR OR GPS RWY 33
				AMDT: 7
				DATED: 07/10/2003