

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
HOLYOKE	FOUR	HOLYO4.NACIK	THREE	15 DEC 2011	21 JUL 2016

TYPE: RNAV SID

DP ROUTE DESCRIPTION:

TAKEOFF RWY 14: CLIMB DIRECT CIPGA, THEN ON DEPICTED ROUTE TO CROSS NACIK AT OR ABOVE 7000.
TAKEOFF RWY 32: CLIMB DIRECT FEKMU, THEN ON DEPICTED ROUTE TO CROSS NACIK AT OR ABOVE 7000.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

TAKEOFF MINIMUMS:
RWY 14, STANDARD.
RWY 32, 300-1 OR STANDARD WITH MINIMUM CLIMB OF 280 FT PER NM TO 4000.
NOTE: RNAV 1.
NOTE: GPS REQUIRED.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 14, TREES 2011 FT FROM DER, 29 FT LEFT OF CENTERLINE, 100 FT AGL/3829 FT MSL.
NOTE: RWY 32, TREES 1009 FT FROM DER, 697 FT LEFT OF CENTERLINE, 100 FT AGL/3839 FT MSL. TOWER 4448 FT FROM DER, 1035 FT LEFT OF CENTERLINE, 165 FT AGL/3886 FT MSL.

CONTROLLING OBSTACLES:

RWY 32: 3886 FT MSL TOWER 403503.31N-1021719.91W

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KHEQ 8E EPOCH YR: 2005
DME/DME ASSESSMENT: NOT CONDUCTED
CHART: TOP ALTITUDE: ASSIGNED BY ATC

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
HOLYOKE	FOUR	HOLYO4.NACIK	THREE	15 DEC 2011	21 JUL 2016

AIRPORTS SERVED:

HOLYOKE, HOLYOKE, CO

COMMUNICATIONS:

KHEQ AWOS-3, DENVER CENTER, UNICOM, DENVER TRACON

FIXES AND/OR NAVAIDS:

VAPUC, NOLCI

REMARKS:

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
HOLYOKE	FOUR	HOLYO4.NACIK	THREE	15 DEC 2011	21 JUL 2016

CHANGES:

ADDED: CHART: TOP ALTITUED: ASSIGNED BY ATC

REASONS:

ATC REQUEST



DEPARTURE (DATA RECORD)

DP Name		Number	DP Computer Code			Superseded Number		Dated	Effective Date
HOLYOKE		FOUR	HOLYO4.NACIK			THREE		15 DEC 2011	21 JUL 2016
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW14 (AER)	403431.06N/1021638.49W	N	-	-	-	-			
CIPGA	403104.60N/1021354.18W	Y	FB	DF		4.02			
VAPUC	402612.95N/1021527.37W	Y	FB	TF	193.72	5.00			
NACIK	402543.62N/1022725.67W	Y	FB	TF	267.01	9.15	AT/ABOVE 7000		
RW32 (AER)	403348.84N/1021604.86W	N	-	-	-	-			CG 280 FT PER NM TO 4000
FEKMU	403847.57N/1022003.13W	Y	FB	DF		5.82			
NOLCI	403437.83N/1022901.50W	Y	FB	TF	238.72	8.00			
NACIK	402543.62N/1022725.67W	Y	FB	TF	172.19	8.98	AT/ABOVE 7000		